



February 2024 Invitation to Submit Competitive Bids For Bryan County EMS – New Ambulance

Bryan County EMS is soliciting competitive, sealed bids from qualified vendors for the purchase of One (1), Type I, Class One (4 x 2), Configuration An ambulance(s) for Bryan County EMS, 306 South 22nd Ave. Durant, OK 74701. Bryan County EMS reserves the right to reject any and/or all bids. Bryan County EMS also reserves the right to accept the bid most advantageous to Bryan County EMS.

The attached specification defines a heavy-duty, commercial emergency medical vehicle, built to withstand adverse driving conditions. The vehicle shall meet or exceed the latest revision to federal specification KKK-A-1822, Federal Motor Vehicle Safety Standards (FMVS.), National Truck Equipment Association (NTEA) Ambulance Manufacturer's Division (AMD) standards and Ford Qualified Vehicle Modifier (QVM) Program Truck Guidelines.

This invitation is extended to all qualified vendors/manufacturers that are specifically in the business of building emergency medical vehicles and/or equipment.

Bryan County EMS reserves the right to increase the number of vehicles purchased without incurring any obligation to obtain bids from other vendors for a period of (1) One year from the date of bid award.

This invitation is issued by:

Bryan County EMS

306 South 22nd Avenue

Durant, OK 74701

Email: invo@bcems.net

PARTY IDENTIFICATION

AGENCY: "Agency" is hereinafter defined as the customer. The customer is an individual or a group of individuals who represent the interest of the city, borough, county, parish, state, or private enterprise and has been charged with the responsibility of purchasing one or more emergency medical vehicle(s).

BIDDER: "Bidder" is hereinafter defined as the vehicle manufacturer and/or its authorized representative. The bidder is an assigned representative who is authorized to commit to a contract with the "Agency".

VENDOR: "Vendor" is synonymous with "Bidder".

NOTICE TO BIDDERS: Bidders shall thoroughly examine any drawings, specifications, schedule, instructions, and any other documents supplied as part of this invitation to bid.

Bidders shall make all investigations necessary to thoroughly inform themselves regarding the content of the written specifications, drawings and instructions supplied herein. No pleas of ignorance by the bidder pertaining to the content of the specifications, drawings, schedule, or instructions will be considered by the agency once the deadline for bid submission has occurred. Failure or omission on the part of the bidder to make the necessary examinations and investigations into the content of the specifications shall not be accepted as a basis for making variations to the spec. Failure or omission by the bidder to make all clarifications or



explanations of exceptions and conditions that exist or that may exist hereafter shall NOT be accepted as a basis for making variations to the **requirements** of the agency or **compensation** to the bidder.

DEFINITIONS:

CLARIFICATIONS: Clarifications shall be **written correspondence** between the bidder, the agency, and all other qualified bidders. A Clarification shall include the paragraph number, page number, the text with unclear content (as written in the specification) and the definition of the clarification requested. Verbal clarifications shall be documented in writing and distributed to all other qualified bidders at least two business days prior to the deadline for bid submission.

EXPLANATION OF EXCEPTIONS: Bidders may take exceptions to any part of the bid contained herein with a written itemized schedule. The schedule shall include the paragraph number(s), the text that the bidder feels he can not comply with an explanation why the bidder feels that the requirement is not in the best interest of the agency and/or an alternate bidder solution. Alternate bidder solutions may be considered by the agency, if the bidder can show the agency that the alternate solution is, in quality and quantity, equal to OR better than the specified item. This agency will share the exception/alternate solution with all other Qualified Bidders. Explanation of exceptions shall be documented in writing at least two business days prior to the deadline for bid submission.

Bidder Complies YES _____ NO _____

CORE DESIGN INTENT: The core design intent of the specifications supplied herein is to purchase an ambulance with the highest level of engineering excellence. The "Core Design" intent of this vehicle shall be centered on the patient's need for pre-hospital care, in conjunction with a safe working environment for the Emergency Medical Personnel.

Bidder Complies YES _____ NO _____

BID PACKAGES SHALL NOT TAKE TOTAL EXCEPTIONS: Bidders are required under this bid invitation to give, for the consideration of the agency, a proposal that will comply with the written specifications, drawings and schedules supplied herein. The specifications supplied represent a compilation of input from all disciplines of users, patients, maintenance, and management personnel who are directly affected by the vehicle's performance.

Careful consideration pertaining to safety, configuration, construction, and workmanship are based on working experiences by all the personnel who have direct, working contact with the subject vehicle specified herein. The "core design" of this ambulance was created because of resolving issues and improvement suggestions that have originated from the personnel most QUALIFIED to make such input.

This agency makes no claim that ALL potential issues or improvements are included in the specifications supplied herein. This agency will consider any VALID concern by any bidder and will consider minor specification exceptions or alternates of equal or better performance, provided that the exception(s) are steered toward meeting the "Core design" intent AND the exception(s) are cleared up not less than two days prior to the bid opening date.



Caution:

A bidder who submits a bid that takes "Total Exception" and makes an offering of some "Standard" or "Stock" unit will be viewed by the agency as a bidder who did not make, and is not prepared to make, a valid bid, and is not qualified to manufacture the ambulance as specified herein. Alternate bids will NOT be considered.

Bidder Complies YES _____ NO _____

VEHICLE QUANTITY: THIS AGENCY is currently seeking to purchase (1) one vehicle per the specifications set forth in this solicitation for bid. Bryan County EMS reserves the right to increase the number of vehicles purchased without incurring an obligation to obtain bids from other vendors for a period of (1) One year from the date of bid award. A contract extension may be provided to the successful, qualified vendor who has performed satisfactorily to the original contract.

Bidder Complies YES _____ NO _____

VENDOR QUALIFICATIONS:

FORD QVM: All Bidders shall be members in good standing of the Ford Motor Company's Qualified Vehicle Modifier Program (QVM). Each bidder shall supply a copy of their valid QVM Certification with their bid package. If for any reason the QVM Certification has been withdrawn or suspended by Ford Motor Company within the past five years, the bidder shall supply a full written explanation as to why it was withdrawn. The written explanation shall include any corrective actions taken to regain the QVM Certification.

NO EXCEPTIONS

Bidder Complies YES _____ NO _____

**FACILITY TO BE ISO 9001:2015
CERTIFIED NO EXCEPTIONS**

Bidder Complies YES _____ NO _____

PRODUCT LIABILITY INSURANCE: Proof of current liability insurance shall be supplied. The proof of insurance shall bear the insurance carrier's name, address, and phone number. The proof shall also bear the name and address of the insured. This document shall contain the coverage schedule, explaining the type of insurance, the policy number, the effective date of coverage, the policy expiration date, and the individual limits.

The minimum amount of coverage shall be as follows:

Commercial General Liability - as follows:

Each Occurrence: \$, 1,000,000

Damage to rented premises, each occurrence: \$300,000 Medical Expenses: \$50,000

Personal and Adv Injury: \$1,000,000 General Aggregate:

\$4,000,000 Products - Comp/OP Agg: \$4,000,000

Automotive Liability - Combined Single Limit: \$1,000,000 Comp/Coll Ded:



\$1,000

Excess Liability - Umbrella Form

Each occurrence: \$5,000,000 Aggregate:

\$5,000,000 Excess Liability: \$20,000,000

Workers Compensation and Employers' Liability

E.L. Each Accident: \$1,000,000

E.L. Disease policy - Each Employee: \$1,000,000

E.L. Disease - Policy Limit: \$1,000,000

Bidder Complies YES _____ NO _____

NON-DISCRIMINATION AND EQUAL OPPORTUNITY: The Bidder/Contractor agrees to comply with all federal statutes relating to non-discrimination. These include but are not limited to:

- (a) Title VI of the Civil Rights Act of 1964 (P.L. 88-352) which prohibits discrimination based on race, color or national origin;
- (b) Title IX of the Education Amendments of 1972, as amended (20 U.S.C. 1681-1683, and 1685-1686), which prohibits discrimination based on sex;
- (c) Section 504 of the Rehabilitation Act of 1973, as amended (29 U.S.C. 794), which prohibits discrimination based on handicaps and the Americans with Disabilities Act of 1990;
- (d) The Age Discrimination Act of 1974, as amended (42 U.S.C. 6101-6107), which prohibits discrimination based on age;
- (e) The Drug Abuse Office and Treatment Act of 1972 (P.L. 92-255), as amended, relating to nondiscrimination based on drug abuse;
- (f) The Comprehensive Alcohol Abuse and Alcoholism Prevention, Treatment and Rehabilitation Act of 1970 (P.L. 91-616), as amended, relating to nondiscrimination based on alcohol abuse or alcoholism;
- (g) 523 and 527 of the Public Health Service Act of 1912 (U.S.C. 290 dd-3 and 290 ee-3), as amended, relating to the confidentiality of alcohol and drug abuse patient records;
- (h) Title VIII of the Civil Rights Act of 1968 (42 U.S.C. 3601 et seq.), as amended, relating to nondiscrimination in the sale, rental, or financing of housing;
- (i) Any other nondiscrimination provisions in any specific statute(s) applicable to any Federal funding for this Agreement;
- (j) The requirements of any other nondiscrimination statute(s) which may apply to

this agreement. Bidder Complies YES _____ NO _____



DRUG FREE WORKPLACE:

The Bidder shall conduct business as a Drug Free Workplace. The Bidder/Manufacturer and ALL its sub-contractors shall provide notice to their employees and sub- contractors as required under the Drug-Free Workplace Act of 1988. A copy of Bidder's Drug-Free Workplace Policy shall be furnished to this agency upon request.

Bidder Complies YES_____NO_____

QUALITY MANAGEMENT SYSTEM REGISTERED: The manufacturer shall have a registration for ISO 9001: 2015 for their Quality Management System (QMS). The QMS provides establishment, documentation, implementation, maintenance, and improvement of management systems that impact the final quality of the product. Registration of the vendor's QMS demonstrates an enduring commitment to quality, a sharp focus on the customer, and robust communication throughout the product process chain to the customer. This registration provides for oversight with routine inspection of the QMS to maintain certification status. Proof of certification shall be readily available upon demand. Proof of Certification shall be provided with bid during initial bid process.

NO EXCEPTIONS

Bidder Complies YES_____NO_____

NATIONAL TRUCK EQUIPMENT ASSOCIATION TESTING

AMD 001 - AMBULANCE BODY STRUCTURE STATIC LOAD TEST: The ambulance described herein shall be type tested to the National Truck Equipment Association's Ambulance Manufacturing Division, Standard 001 - Ambulance Body Structure Static Load Test except the test weight shall be a minimum of 55,000 pounds. The test shall be conducted by an independent testing laboratory. The module body bid herein shall contain extrusion shapes and general structural layout identical to the test body used in the test.

AMD 002 - BODY DOOR RETENTION COMPONENTS TEST: The ambulance described herein shall be type tested to the National Truck Equipment Association Ambulance Manufacturing Division, Standard 002 Body Door Retention Components Test. The test shall be conducted by an independent testing laboratory. The module body bid herein shall contain identical door extrusion shapes, door skin configuration and general structural layout as the test body used in the test.

Safety is this Agency's first concern. Entry and compartment door integrity is crucial to the safety of the patient, public, passengers and crew. If the Bidder has experienced any of the following door conditions as a result of collision, rollover or other accidental impact, then the Bidder shall supply the Agency with a report containing the date, a full explanation of the incident and corrective actions taken.

- A) Any entry door rendered inoperative.
- B) Any door that has come open.
- C) Foreign object penetration into patient cabin through the body structure.

Catastrophic door failure during a collision indicates mechanical defects in the design, hardware and/or the



direct construction of the modular door. Any AMD Standard 002 testing prior to the incident is deemed invalid, regardless of the expiration date of the original test.

AMD 003 - OXYGEN TANK RETENTION SYSTEM STATIC TEST:

The ambulance described herein shall be type tested to the National Truck Equipment Association Ambulance Manufacturing Division, Standard 003

- Oxygen Tank Retention System Static Test. The test shall be conducted by an independent testing laboratory.

Safety is this Agency's first concern. Main cylinder control is extremely important and is crucial to the safety of the patient, public, passengers and crew. If the Bidder has experienced a cylinder rack separation from the oxygen compartment wall, OR if the cylinder has come loose from the cylinder restraining device, then the Bidder shall supply the Agency with a report containing the date, a full explanation of the incident and corrective actions taken to prevent future failures. Main Oxygen/Air Cylinders that come loose during a collision indicate mechanical defects in the design of the restraining device or the mounting method. Any AMD Standard 003 testing prior to the incident is deemed invalid, regardless of the expiration date of the original test.

AMD 004 - LITTER RETENTION SYSTEM STATIC TEST: The cot/litter retention system described herein shall be tested to the National Truck Equipment Association, Ambulance Manufacturing Division Standard 004

- Litter Retention System Static Test. The cot mount hardware, mounting method and floor reinforcement areas shall exceed the test as described in AMD 004. This test shall be conducted by an independent testing laboratory.

Safety is this Agency's first concern. Main cot/litter retention is critical to patient care. If the Bidder has experienced a litter ejection due to a hardware defect or a defect in the mounting method, then the Bidder shall supply the Agency with a report containing the date, a full explanation of the incident and corrective actions taken to prevent future ejections. Main Cot/Litter ejection's that occur during a collision indicates mechanical defects in the design of the restraining device or the mounting method; Therefore, ALL Bidder AMD Standard 004 testing dated prior to the incident is deemed invalid, regardless of the expiration date of the original test.

AMD 005 - 12-VOLT DC ELECTRICAL SYSTEMS TEST: The 12-Volt DC Electrical System described herein shall be tested to the National Truck Equipment Association, Ambulance Manufacturing Division Standard 005 - 12-Volt DC Electrical Systems Test. This test is valid for the test article vehicle ONLY. The test shall be conducted on EACH ambulance. The results of the test shall be recorded on an electrical system performance sheet and shall be included with the delivery documents. This test shall be conducted by a qualified quality control electrician at the ambulance manufacturing plant.

Reliability and Safety is this Agency's first concern. The 12-volt electrical system must be functional under all normal or adverse driving and operating conditions. Each electrical device, electrical component, wire, wire route and connection quality shall be tested for reliability as a "SYSTEM" on each vehicle sold. If the Bidder has experienced an electrical fire or an electrical failure resulting in a disabled ambulance going to an emergency call or during transportation, shall supply the Agency with a report containing the date, a full



explanation of the incident and corrective actions taken to prevent future electrical failures.

AMD 006 - PATIENT COMPARTMENT SOUND LEVEL TEST: The ambulance described herein shall meet or exceed the National Truck Equipment Association Ambulance Manufacturing Division Standard 006 Patient Compartment Sound Level Test. The sound level in the driver or patient cabin shall be eighty decibels or less under the conditions described in AMD Standard 006.

AMD 007 - PATIENT COMPARTMENT CARBON MONOXIDE LEVEL TEST: The ambulance described herein shall meet or exceed the National Truck Equipment Association, Ambulance Manufacturing Division Standard 007 - Patient Compartment Carbon Monoxide Level Test. The patient and driver cabin shall be environmentally sealed from carbon monoxide gases that are emitted from internal combustion engines. The ambulance specified herein shall have safe carbon monoxide levels of ten parts per million or less while the vehicle is exposed to the conditions described in AMD Standard 007.

AMD 008 - PATIENT COMPARTMENT GRAB RAIL STATIC LOAD TEST: The patient cabin grab rails shall be tested to the National Truck Equipment Association, Ambulance Manufacturing Division Standard 008 - Patient Compartment Grab Rail Static Load Test. The ceiling mounted grab rails shall be subject to a three axis load of three hundred pounds.

The ceiling mounted grab rail shall not come loose from the ceiling or permanently deform. All mounting fasteners shall be threaded into metal structure not less than .125 inches thick.

AMD 009 - 125-VOLT AC ELECTRICAL SYSTEMS TEST: The patient cabin shall be wired per the National Truck Equipment Association, Ambulance Manufacturing Division Standard 009 - 125 -Volt AC Electrical Systems Test.

The ambulance wiring shall comply with the National Electric Code in effect at the time of manufacture of the ambulance. The system specified herein shall be a 2-wire system with a ground. All outlets and 120-volt hard wired devices, on the ambulance, shall have ground fault interrupter protection.

AMD 010 - WATER SPRAY TEST: The ambulance specified herein shall be water spray tested for water leakage into the patient's and driver's cabins. The door to jamb seal, window installation and seals shall be tested against leakage per the National Truck Equipment Association, Ambulance Manufacturing Division Standard 010 - Water Spray Test. This test shall be conducted on EACH ambulance by the quality assurance department.

AMD 011 - EQUIPMENT TEMPERATURE TEST: The ambulance and equipment specified herein shall operate satisfactorily operate between 30 degrees and 125 degrees Fahrenheit per the National Truck Equipment Association, Ambulance Manufacturing Division Standard 011 - Equipment Temperature Test. This standard must be type certified by an independent testing laboratory on a like test model.

AMD 012 - INTERIOR CLIMATE CONTROL TEST: The ambulance and equipment specified herein shall be equipped with a HVAC (Heating, Ventilation, and Air Conditioning) System that will meet or exceed the performance criteria set forth in the National Truck Equipment Association, Ambulance Manufacturing



Division Standard 012 - Interior Climate Control Test. This standard must be type certified by an independent testing laboratory on a like test model.

AMD 013 - WEIGHT DISTRIBUTION GUIDELINES: The ambulance specified herein shall be weighed at the end of the ambulance manufacturer's production cycle to assure compliance with the National Truck Equipment Association, Ambulance Manufacturing Division Standard 013 - Weight Distribution Guidelines.

The vehicle specified herein must be weighed on a four-point scale that measures the weight imposed on EACH wheel. The side-to-side weight difference tolerance shall not exceed five percent (5%).

The total weight imposed on the FRONT axle shall not exceed the chassis manufacturer's gross axle weight rating minus three hundred pounds.

The total weight imposed on the REAR axle shall not exceed the chassis manufacturer's gross axle weight rating minus one thousand pounds.

The aggregate total of all four points shall not exceed the gross vehicle weight rating minus eleven hundred pounds regardless of customer specified equipment.

AMD 014 - ENGINE COOLING SYSTEM TEST: The cooling system in the ambulance specified herein shall be tested to assure compliance with the National Truck Equipment Association, Ambulance Manufacturing Division Standard 014 - Engine Cooling System Test. The vehicle specified herein must be tested at the end of the ambulance manufacturers manufacturing cycle to determine if the cooling system capacity is adequate to maintain safe engine operating temperature at ninety-five degrees, ambient temperature for one hour. EACH ambulance shall be checked to assure a leak and trouble-free cooling system performance.

AMD 015 - AMBULANCE MAIN OXYGEN SYSTEM TEST: Each ambulance's main Oxygen System shall be tested to assure compliance with the National Truck Equipment Association, Ambulance Manufacturing Division Standard 015 - Ambulance Main Oxygen System Test. The subject vehicle specified herein must be equipped with an Oxygen system that can withstand a 150 PSI charge of dry air or Nitrogen for a period of four hours without a loss exceeding five pounds per square inch of pressure. The results of this test shall be posted inside the oxygen tank stowage compartment. A certificate shall be supplied, describing the test conditions, the initial test pressure, the final pressure (after four hours) and the name of the inspector who performed the test.

AMD 016 - PATIENT COMPARTMENT LIGHTING LEVEL TEST: The ambulance and equipment specified herein shall be equipped with patient compartment lighting that will meet or exceed the performance criteria set forth in the National Truck Equipment Association, Ambulance Manufacturing Division Standard 016 - Patient

Compartment Lighting Level Test. This standard must be type certified by an independent testing laboratory on a like test model.

AMD 017 - ROAD TEST: The ambulance and equipment specified herein will meet or exceed the



performance criteria set forth in the National Truck Equipment Association, Ambulance Manufacturing Division Standard

017 - Road Test. This standard must be type certified by an independent testing laboratory on a like test model.

AMD 018 - REAR STEP AND BUMPER STATIC LOAD TEST: The rear step and bumper shall be type tested to the National Truck Equipment Association, Ambulance Manufacturing Division Standard 018 - Rear Step and Bumper Static Load Test. This standard must be type certified by an independent testing laboratory on a like test model.

AMD 019 - MEASURING GUIDELINES: COMPARTMENTS AND CABINETS: The ambulance specified herein shall be in compliance with the National Truck Equipment Association, Ambulance Manufacturing Division Standard 019 - Measuring Guidelines: Compartments and Cabinets.

AMD 020 - FLOOR DISTRIBUTED LOAD TEST: The ambulance specified herein shall be type tested to the National Truck Equipment Association, Ambulance Manufacturing Division Standard 020 - Floor Distributed Load Test. This standard must be type certified by an independent testing laboratory on a like test model.

AMD 021 - ASPIRATOR SYSTEM TEST, PRIMARY PATIENT:

Each ambulance's primary patient aspirator system shall be tested to assure compliance with the National Truck Equipment Association, Ambulance Manufacturing Division Standard 021 - Aspirator System Test, Primary Patient.

AMD 022 - COLD ENGINE START TEST:

The ambulance specified herein shall be type tested to the National Truck Equipment Association, Ambulance Manufacturing Division Standard 022 - Cold Engine Start Test.

AMD 023 - SIREN PERFORMANCE TEST:

The ambulance siren system shall be type tested to the National Truck Equipment Association, Ambulance Manufacturing Division Standard 023 - Siren Performance Test.

AMD 024 - PERIMETER ILLUMINATION TEST:

The ambulance and equipment specified herein shall be equipped with perimeter lighting that will meet or exceed the performance criteria set forth in the National Truck Equipment Association, Ambulance Manufacturing Division Standard 016 - Perimeter Illumination Test. This standard must be type certified by an independent testing laboratory on a like test model.

AMD 025 - MEASURING GUIDELINES: OCCUPANT HEAD CLEARANCE ZONES:

The ambulance specified herein shall be in compliance with the National Truck Equipment Association, Ambulance Manufacturing Division Standard 025 - Measuring Guidelines: Occupant Head Clearance Zones.

Bidder Complies YES _____ NO _____

CRASHWORTHINESS:

Safety is a primary objective for modular ambulance vehicles produced under this specification. In addition



to compliance with design criteria incorporated herein, manufacturer shall also provide certified documentation to provide proof of crash worthiness of vehicle(s) proposed.

Crash worthiness of vehicle shall be demonstrated through a minimum of two actual crash tests of modular body ambulance under laboratory conditions. These crash tests will be similar in scope to testing performed by the National Highway Traffic Safety Administration and the Insurance Institute for Automobile Safety to verify the crash worthiness of passenger vehicles. An independent test laboratory accepted and utilized by the National Highway Traffic Safety Administration for their crash tests shall perform this testing and provide certification. Testing shall be performed and verified by SAE Member Engineers.

Test criteria shall be defined as a minimum of two actual high-speed impact crash tests between an ambulance and mid-size passenger vehicles. Collisions shall be into each side of manufacturer's standard production modular ambulance body mounted on a chassis, struck by an actual bullet vehicle. Crash energy at impact shall be a minimum of 3,000 pounds at 42 miles per hour.

Reports from crash testing shall be certified by testing lab, and shall include the following minimum results:

- 1) The required six-point medic restraint system shall hold all attendants in their seats. There shall be no head contact with anything except head rests. There shall be no excessive excursion of the attendants in their seats regardless of which way they were facing.
- 2) The ambulance body structure shall remain intact after both impacts. Bending of body shall be localized to point of impact, and doors adjacent to the actual crash point shall continue to operate. There shall be no intrusion into the patient compartment.
- 3) The body mount and pucks shall remain intact as a result of the impacts. There shall be no visual damage to body mounts or floor structure.
- 4) All interior cabinetry and fixtures shall remain in place and undamaged.

This provision requires actual crash testing of an ambulance by high-speed moving vehicles to validate safety and crash worthiness. Crash simulations, acceleration testing, sled testing, barrier testing or other theoretical tests are not sufficient to meet this requirement. Certified documentation from a qualified independent testing laboratory shall be provided with the bid in order to validate compliance with this requirement.

NO EXCEPTIONS

Bidder Complies YES _____ NO _____

QUALITY ASSURANCE:

The vendor shall inspect and test all systems, electrical loads, per current Federal specification KKK-A-1822 Section 4. Testing results shall be documented and displayed in the Oxygen compartment and/or supplied with the delivery handbook.

QUALITY/COMPLIANCE ASSURANCE:

Bryan County EMS
306 South 22nd Avenue
Durant, Oklahoma 74701
580-924-4687



A thorough quality/compliance inspection by this agency's employees or this agency's hired representative shall compare the Ambulance to the specifications within 10 calendar days of written notice of vehicle completion by the successful bidder. The notice may be faxed, followed by phone contact. The customer reserves the right to authorize the bidder's DEALER to conduct the inspection provided the DEALER is authorized and qualified to correct quality/compliance issues at the DEALER site.

Bidder Complies YES _____ NO _____

NON-COLLUSIVE BID CERTIFICATION:

By submission of this bid response, the Bidder and/or the Bidder's authorized representatives, certify under penalty of perjury, that to the best of their knowledge and belief the following:

- A) The prices in the bid response have been arrived at independently without collusion, consultation, communication, or agreement for the purpose of restricting competition, as to any matter relating to such prices with any other Bidder or with any competitor, and;
- B) Unless otherwise required by law, the prices which have been quoted in the bid response have not knowingly been disclosed by the Bidder and will not knowingly be disclosed by the bidder, prior to the public bid opening, either directly or indirectly to any competitor, and;
- C) No attempt has been made or will be made by the Bidder, for the purpose of restricting competition, to induce any person, partnership or corporation not to submit a bid response.

Bidder Complies YES _____ NO _____

DEBARMENT STATUS:

By submission of this bid response, the Bidder and/or its authorized representatives, certify under penalty of perjury, that to the best of their knowledge and belief they are not currently debarred from submitting bids or bid on contracts by any agency within the home state of THIS AGENCY, nor are they an agent of any person or entity that is currently debarred from submitting bids on contracts by any agency within the home state of THIS AGENCY.

WARNING:

This agency will not tolerate Vendors who state compliance to specifications but deliver an incomplete product and/or sub-standard materials and workmanship. Vendors who have made delivery of such an ambulance without making every reasonable effort to remedy the defects found at the time of delivery or within the warranty period will be notified that they are DEBARRED from submitting bids to this agency in the future.

This agency will not waste valuable time (more than once) trying to recover legal costs and deal with lost in-service time of new apparatus, working with vendors who are unresponsive to the needs of this agency.

Bidder Complies YES _____ NO _____



CHASSIS

TYPE I AMBULANCE: The apparatus shall be a Configuration A, 2-door, conventional cab, and chassis with a transferable, modular, ambulance body.

Bidder Complies YES _____ NO _____

CHASSIS MAKE:

The apparatus shall be mounted on a commercially available cab and chassis. The chassis manufacturer shall be the vehicle's point of origin. The chassis shall be supplied as an incomplete vehicle to the successful ambulance manufacturer. The chassis supplied shall conform to all applicable Federal Motor Vehicle Safety Standards in force at the time of manufacture. A statement of conformity shall be supplied with the chassis in an "Incomplete Vehicle Manual".

CHASSIS MODEL:

The apparatus shall be mounted on a 2023 or newer, Regular cab, dual rear wheel, two-wheel drive chassis equipped as follows below.

OEM:

The acronym OEM is Original Equipment Manufacturer. The OEM is the chassis manufacturer and the vehicles Maker and Origin.

TRIM LEVEL:

The cab shall be equipped with an "XLT" type Trim level with tilt steering wheel, cruise control, power windows and door locks. The front bumper and grill shall be black in color NO CHROME. The OEM grille work shall remain OEM. After-market vacuum formed, proprietary grille work made by the ambulance manufacturer is not acceptable due to replacement part cost and lack of immediate availability.

Bidder Complies YES _____ NO _____

ENGINE:

Turbo-Charged Diesel engine shall be provided with a minimum displacement of 6.7 liters (402 cu in). The engine output shall be 330 horsepower at 2,600 revolutions per minute and deliver 750 foot pounds of torque at 2,000 revolutions per minute. The compression ratio of the engine is 16.2:1 with a high pressure common rail fuel injection system. Engine performance shall comply with or exceed the most current revision of KKK-A-1822.

Bidder Complies YES _____ NO _____

TRANSMISSION:

There shall be a Heavy-Duty Torque shift, 10-speed, automatic transmission with overdrive provided.

Bidder Complies YES _____ NO _____



CAB INTERIOR COLOR:

The color of the cab interior shall be gray. Bidder Complies YES___ NO___

GROSS VEHICLE WEIGHT RATING (GVWR):

The GVWR of the chassis supplied shall be at least 16,500 pounds.

Bidder Complies YES___ NO___

FRONT AXLE WEIGHT RATING (FAWR):

The FAWR shall be rated no less than 7,000 pounds. Bidder Complies YES___ NO__

REAR AXLE WEIGHT RATING (RAWR):

The RAWR shall be rated no less than 12,880 pounds.

Bidder Complies YES___ NO___

CAB SEATS:

OEM high back, velour covered bucket type seats shall be provided in the cab. The seats shall adjust forward and aft. Seat base must be OEM. After market seats and/or bases are not acceptable due to violations regarding SRS (Air Bag) deployment geometry and Ford QVM Guidelines.

Bidder Complies YES___ NO___

OCCUPANT RESTRAINT SYSTEM:

The front, forward facing cab seats shall be equipped with OEM installed three-point seat belts. The seat belt assemblies shall meet or exceed FMVS. 208 and 209. The inside conversion panels shall not interfere with the swivel arc of the shoulder rings.

Bidder Complies YES___ NO___

SUPPLEMENTAL RESTRAINT SYSTEM:

An OEM air bag shall be installed on the driver and passenger side. Permanent or Quick release ambulance conversion components shall not interfere with air bag deployment. The air bags must be completely operational. Modifications by the secondary manufacturer are not acceptable.

Bidder Complies YES___ NO___



SPARE TIRE:

One (1) spare tire and wheel assembly shall be supplied. Bidder

Complies YES _____ NO _____

SPARE TIRE STOWAGE LOCATION: The spare tire and wheel assembly will not be carried on the unit. The spare tire and all the related tools, if supplied by the OEM, shall be shipped loose with the completed vehicle.

Bidder Complies YES _____ NO _____

JACK AND SPARE TIRE TOOLS: The vehicle jack and tools associated with the spare tire and jack shall be installed loose not mounted in the cab to be moved later.

Bidder Complies YES _____ NO _____

WHEEL/RIM APPEARANCE:

All 6 wheels will be steel wheels coated with powder coated, matte black in color, inside and outside of rims. No simulators.

Bidder Complies YES _____ NO _____

BRAKES:

4-wheel anti-lock, power assisted hydraulic brakes shall be supplied by the OEM. The brakes shall be 4-wheel Disc type with Dual piston, Pin slider calipers. The front disc diameter shall be 14.53 inches in diameter and the rear disc shall be 15.55 inches in diameter. The parking brake shall be a foot operated, hand release independent mechanical brake, provided by the OEM.

Bidder Complies YES _____ NO _____

BRAKE BOOSTER / ANTI LOCK SYSTEM:

The brake pedal effort shall be reduced by a hydro-boost power assist unit. The booster shall be installed on the fire wall and linked directly to the foot pedal. Hydraulic brake pressure shall route through a 3-channel, 4-Wheel anti-lock brake system that prevents wheel lock-up.

Bidder Complies YES _____ NO _____

INTERIOR UPGRADE PACKAGE:

Ford interior upgrade package shall be ordered and supplied on the chassis. This package shall include:

- Cloth Headliner
- High trim door panels



Ford option code 21A high back bucket seats Cloth sun visors

Power Door locks Power

Windows Insulation package

Bidder Complies YES _____ NO _____

FLOOR PEDALS:

The chassis shall have OEM adjustable floor pedals, option 62M.

Bidder Complies YES _____ NO _____

DAYTIME RUNNING LIGHTS:

Daytime running light option No 942 shall be supplied and installed by the OEM. Both headlights shall come on with the ignition

switch. Bidder Complies YES _____ NO _____

SHOCK ABSORBERS:

The chassis supplied shall be equipped with one shock absorber for each side of each axle. An OEM selected one and three eighth (1-3/8") inch gas type shock shall control vehicle spring oscillation and dampen road related jounce and harshness. Ambulance related shields, floor members or other devices shall not interfere with shock replacement.

Bidder Complies YES _____ NO _____

FRONT STABILIZER BAR:

A computer selected; one-inch diameter anti-sway bar shall be supplied. The bar shall regulate body shift and enhance drivability, handling, and control. The solid torsion spring steel bar shall be attached to the vehicle frame utilizing natural rubber bushings and removable steel bushing housings. The ends of the bar shall be inserted into natural rubber bushings, located near the front wheels. Both axle attachment points shall be cast into the forged steel, I-beam front axle.

Bidder Complies YES _____ NO _____

FUEL TANK:

The fuel capacity shall be at least 40 US gallons. The fuel range shall be at least 250 miles per KKK-A-1822.

Bidder Complies YES _____ NO _____



REAR AXLE TYPE AND RATIO:

The axle shall be Limited Slip Differential with a 4.10:1 gear ratio. Ford Code XG8.

Bidder Complies YES _____ NO _____

TIRES:

All mounted, active tires shall be identical make, tread type, size and load range. For the aforementioned GVWR the tires shall be LT225/70Rx19.5 load range F. A label with the recommended tire pressure shall be located above each wheel opening, unless specified otherwise by the purchaser. All tires shall be balanced per KKK-A-1822 3.6.12.

Bidder Complies YES _____ NO _____

AMBULANCE PREPARATON PACKAGE:

The chassis provided shall be equipped with an ambulance preparation package designed and installed by the OEM.

The 47L allows operator commanded regeneration down to 30% DPF capacity. The 47A had to have at least 70% DPF capacity to do a manual regeneration. The low-DEF fluid will not cause the vehicles speed limiting or forced idle. It will still give you the warning lights, chimes, and message. The 47L is a Federal Emissions compliant package. *It is not certified in California or the Green States.* California has declared to NTEA/AMD that they do not regulate emergency vehicles. The package shall be designed to hold up to the demands and duty cycles inherent with Emergency Medical Vehicles.

Bidder Complies YES _____ NO _____

ALTERNATOR - CHARGING SYSTEM:

Two alternators shall be supplied and installed by the OEM. The alternators shall be as supplied by Ford under the 47L/A Ford Ambulance Prep option. Both alternators shall be controlled by the vehicles on board computer. The ambulance manufacturer shall not modify the OEM. computer's functional control of the alternators. The alternators' output cable, originally connected directly to the positive post of the under-hood battery, shall be rerouted to a 3/8" diameter, solid brass junction post. A 2/O positive battery cable shall reconnect the alternators to the batteries from the junction post. The ambulance load cable shall connect under the hood to the aforementioned junction post.

Bidder Complies YES _____ NO _____

THROTTLE HIGH IDLE:

A programmable OEM throttle control shall be provided. The throttle shall be programmed for charge protect. The throttle control module shall be located in the ambulance manufacturer's center cab console. The throttle shall be easily accessible through removable face panels. Program buttons shall not be readily accessible to end users.

Bidder Complies YES _____ NO _____



CAB STEREO:

An OEM AM/FM/CD in dash radio with Sync 4 touch screen and four cab mounted speakers shall be included with the chassis. Radio to have an integrated application to allow phone to connect to radio and utilize phone navigation or have an integrated navigation system installed.

Bidder Complies YES_____ NO_____

CHASSIS VOICE CONTROL SYNCH:

The chassis manufacturer shall include a SYNCH option which will allow for greater safety of the vehicle driver. The driver shall be able to voice control and connect to multiple wireless systems. The driver of the vehicle shall refer to the owner's manual for details of the operation.

Bidder Complies YES_____ NO_____

MIRRORS:

Dual OEM, Power adjusted mirror glass, manually telescoping Black mirrors, shall be mounted to the forward, lower corner of the cab door window. Both mirrors shall feature a bi-directional break-away function to permit folding the mirror heads against body in close quarters. The mirrors shall be seven inches wide by eight inches high and flat on both right and left sides.

Bidder Complies YES_____ NO_____

REAR KNEELING SUSPENSION:

A Liquid Spring type rear hydraulic strut suspension shall be installed in lieu of the standard rear OEM single stage leaf springs. The suspension company shall be QS 9000 and ISO 9001 certified for excellence. The liquid suspension shall be rated at 12,000 pounds GAWR and installed per Liquid Spring Directions. Suspension Installation instructions and drawings shall be followed. All guidelines regarding chassis and axle capacity ratings as published by Ford Motor Corporation shall be adhered to

MECHANICAL SUSPENSION COMPONENTS:

The control arms shall be connected to a replacement front hanger that features upper and lower control arm pivot points and a connection point for a heavy-duty sway bar. Both Liquid Spring struts shall be positioned directly aft of the axle and outboard of frame rails. The designed ride height shall maintain original suspension's drive-line geometry.

TRACKING BAR:

The suspension shall utilize a lateral control rod (tracking bar) to maintain side to side axle position related to the chassis frame. Wear shoes, mounted to the sides of the frame rails are not acceptable.

HYDRAULLIC SYSTEM:

All hydraulic lines, fittings, reservoirs, and valves shall be protected against "stone pecking". Abrasion covers,



such as nylon convolute loom over the lines are required. The entire assembled system shall be tested for leaks at every fitting connection point.

MECHANICAL QUALITY ASSURANCE:

All fasteners related to the suspension assembly are considered critical. All fasteners shall be tightened to the manufacturer's recommended torque by the primary installation mechanic. A secondary mechanic shall "put a wrench" and re-torque ALL of the fasteners and then spray a contrasting color of paint onto the heads and nuts of each fastener.

SUSPENSION JOUNCE STUDY:

A suspension jounce clearance study shall be performed throughout the full range of suspension travel to ensure adequate clearance of suspension, frame, and brake components. Test results shall be documented and supplied in the owner's manual.

Bidder Complies YES_____ NO_____

REAR STABILIZER BAR:

The rear sway bar shall remain OEM. Bidder Complies YES
_____ NO _____

KNEELING FEATURE ENABLE:

The rear suspension shall kneel when the triggering device is activated AND an enable switch, located in the cab console is activated.

Bidder Complies YES_____ NO_____

KNEELING FEATURE ACTIVATION:

The kneeling feature shall activate in PARK position with parking brake set. The kneeling feature shall NOT activate in any forward or reverse gear. The above rear suspension shall kneel when the trailing rear access door is opened. The Kneeling function will not be connected to the High Idle. A stop switch will be mounted inside the Back doors of the patient compartment on the Passenger side to the left side of the door.

Bidder Complies YES_____ NO_____

VEHICLE EXHAUST TERMINATION POINT:

The exhaust system routing shall remain unmodified, and the termination point shall remain after the rear axle on the right side. Shall be coated in polyurethane black.

Bidder Complies YES_____ NO_____



VACUUM PUMP:

There shall be a vacuum pump to activate the Patient Area "Heater Control Valves" when the patient area heater is energized. The electrical layout shall be shown on the custom wiring schematics at the time of delivery.

Bidder Complies YES _____ NO _____

TIRE VALVE EXTENDERS:

One pair of tire valve extenders shall have been supplied and installed for each inside rear wheel. The tire valve extenders shall permit the user to check tire pressure and fill the inside rear tires without removing the outer tire. The extenders shall have a braided stainless steel outer jacket to resist abrasions and cuts. The filler end shall be supported by a valve bracket.

Bidder Complies YES _____ NO _____

MODULE CONSTRUCTION - GENERAL

SERVICE INTENT:

The ambulance body shall be all aluminum. The body sheet shall be reinforced with structural members designed to resist deflection and hold up to extreme ambulance service per the latest revision of federal specification KKK-A-1822.

BODY MEMBER ALLOY:

The side, roof, front, and rear sheet shall be derived from .125", 5052-H-32 aluminum sheet. The roof sheet shall be one (1) piece, .090", from roof rail to roof rail. The side structure and structural shapes shall be extruded of 6105-T5 aluminum.

STRUCTURAL INTEGRITY:

The body shall be capable of providing impact, deformation, and penetration resistance in the event of a collision. The body structure shall be capable of passing a standalone static load test on a type-tested body. The test shall be conducted in accordance with AMD- 001 **except the test weight shall be a minimum of 55,000 pounds**. The same unit shall be subjected to the same test with the body turned on its side. A complete copy of the testing documents with photos must be supplied upon bid review if requested by this agency. Non-compliant bids will be rejected.

WELD QUALITY:

All welds within the modular body shall meet American Welding Society codes for structural and sheet welding. Compliance documentation must be supplied upon bid review if requested by this agency.

CREVICE PREPARATION:

All skin and extrusion surfaces destined to be mated together, shall be primed with epoxy, etching primer prior to assembly. All over lapping extrusion to skin surfaces shall be bedded with a two-part acrylic high



strength bonding adhesive.

SIDE STRUCTURAL MEMBERS:

The sheet edges will be fit into slots designed within a proprietary, double hollow, corner post extrusion in addition to the two-part acrylic bonding agent. The sheet will be MIG welded and structurally bonded to the extrusion. Double-hollow designed corner post extrusions shall be used to weld the side and end assemblies together. Horizontally oriented, adjoining structural box tubes shall be welded to the corner post with a minimum 50% surface weld. The intermediate structural members of the side grid shall be two (2) inch by two (2) inch 6105-T5 aluminum, architectural box tubing. All entry and compartment door adjacent members shall be one quarter (1/4") inch, two (2) inch by two (2) inch proprietary extruded shape. The main structure shall

surround the compartment openings and provide intermediate skin support. The intermediate structure spacing shall have a nominal dimension of twelve (12) inches. All grid structure shall be welded together with a minimum of 75% of available mating surface. The side skin shall be bonded to the structural grid using (1.75") wide, VHB (Very High Bond) adhesive tape. The edges of the tube that touch the skin will be sealed with Bostik Brand, Simson ISR 70-03 Construction Adhesive.

SIDE IMPACT RAILS:

There shall be four (4) side impact rails, located in the upper and lower sections of the side walls. They shall consist of 6105-T5 aluminum, that is solid half (1/2) inch thick by four (4) inch plate on the curbside and one-half (1/2) inch by four (4) inch plates on the streetside that are continuously MIG welded, or Huck structurally fastened to the structural grid. Since this is a safety item, no exceptions will be accepted.

SEAT BELT ANCHORAGE:

Occupant seat belts shall be drilled and tapped through one-half (1/2) inch by four (4) inch plate on the curbside and one-half (1/2) inch by four (4) inch plates on the streetside that are continuously MIG welded to the structural grid. Since this is a safety item, no exceptions will be accepted.

SIDE SHEET:

The side sheet shall be .125 thick, 5052-H32 aluminum. The side sheet compartment opening cut outs shall be cut with CNC controlled, gantry mounted plasma or high-speed routing equipment. The door opening shall be cut to allow for the skin to be molded into the jamb opening to create a crevice free jamb with a smooth paint finish. The machine formed skin shall return into the body at least 3/4" to meet the jamb extrusion. This method will encourage square openings to receive the door assemblies and maintain critical structural locations. The door jamb shall have a full structure frame behind the jamb skin return. It shall not rely strictly on the skin for the compartment jamb.

Pre-determined ventilation louvers shall be *formed* into the body sheet, where specified. *A seamless door jamb exterior is required to minimize corrosion. Extruded type exposed door jambs do not meet this specification. The skin shall completely conceal the doorjamb from view.* The only visible seams on the body sheet shall be at the corner posts. The skin shall extend .688" below the skirt rail extrusion to a drip edge to keep moisture from collecting underneath where the skin meets the skirt rail extrusion.



CORNER POST EXTRUSION:

The corners of the modular body shall be made from an extruded aluminum structure that has an alloy of 6063-T6. The corner post extrusion shall be 3.25" x 3.25" with a 2" radius on the outer corner. The corner post extrusion shall have an internal web member that runs on a 45-degree angle to the front and side of the modular body. Where the internal web meets the exterior extrusion wall the internal web shall flair into a .125" radius giving a .25" wall thickness at the exterior wall of the extrusion. There shall be a .75" flange on each side of the corner post extrusion that is a side skin receiver. The side skin receiver shall be funnel shaped to allow the exterior side skin to fully seat into the corner post extrusion. The interior walls of the corner post extrusion shall be .125" thick and they shall incorporate a 45-degree weld bevel on the interior corners.

REAR SILL EXTRUSIONS:

The rear body and floor substructure shall be constructed of a dual proprietary aluminum extrusion with mating joints. The lower floor extrusion is a combination continuous extrusion with an incorporated L mating surface. The lower door extrusion is a multi-chamber construction with matching radius corner and surfaces to the floor sill. This combination of extrusion and joint structure provides for strong joint strengths, and continuous contact surface between the floor sill and the outer-body door extrusion.

FRONT AND SIDE WALL GUSSET PLATES:

The front wall and side wall structural members shall have additional support with a fully welded gusset system that shall be made of 5052-H32 aluminum plate, one quarter (1/4) inch thick by four (4) inches by four (4) inches.

REAR AND SIDE WALL GUSSET PLATES:

The rear wall and side wall structural members shall have additional support with a fully welded gusset system that shall be made of 5052-H32 aluminum plate, one quarter (1/4) inch thick by four (4) inches by four (4) inches.

ROOF RAIL EXTRUSIONS:

The roof corners of the modular body shall be made from an extruded aluminum structure that has an alloy of 6063-T6. The roof rail extrusion shall be 4.55" x 3.5" with a 2" radius on the outer corner. A full-length drip rail shall be incorporated into the roof rail corner post extrusion, drip rails at the top of the modular body that are not inclusive of the roof rail extrusion do not meet the intent of the specification and are deemed non-compliant to this specification. The roof rail extrusion shall have an internal web member that runs on a 45-degree angle to the front and side of the modular body. Where the internal web meets the exterior extrusion wall the internal web shall flair into a .125" radius giving a .25" wall thickness at the exterior wall of the extrusion. There shall be a .75" flange on the lower side of the roof rail extrusion that is a side skin receiver. The side skin receiver shall be funnel shaped to allow the exterior side skin to fully seat into the roof rail extrusion. There shall be a .75" x .125" recess into the roof side of the extrusion for locating the roof sheeting. This recess shall have a 45-degree weld bevel. The interior wall of the roof rail extrusion that is in-board of the side skin funnel shall be 2" wide so that they line up with the exterior side wall. The interior wall of the roof rail extrusion that is in-board of the roof sheeting recess shall be 2.25" wide so that they line up with the 2.25" roof bows. The interior walls of the roof rail extrusion shall be .125" thick and they shall incorporate a 45-degree weld bevel on the interior corners.



ROOF SHEET:

The four (4) edges of the sheet shall be continuously welded to the roof rail extrusion to prevent leaks. All perimeter welds shall be ground smooth and worked smooth prior to the overall body paint and finish. Non-fully welded roof sheets to the roof rail extrusions do not meet the intent of this specification and are deemed non-compliance to this specification.

ROOF BOWS:

The roof sheet shall be supported by full width .125" x 2" x 2.25" architectural box tubing. The roof bows shall be located on twelve (12) inch centers. The roof bows shall be MIG welded to the roof rail extrusions with no less than four (4) and one-half (1/2) inches of continuous weld per end. The roof sheet shall be bonded to the roof bows with VHB (Very High Bond) adhesive tape.

LATERAL ROOF SUPPORTS:

If this agency requires ducted ceiling HVAC, additional structural support will be added as a result of the 2" ducted heat and A/C delivery system. 2" x 2" three-sided extruded channel with two sides being .125" thick and the bottom surface for fastener acceptance to be .160" shall be full length of the body.

ROOF CORNERS:

The roof rail extrusions shall be welded together along the roof bow mating walls at the corners. In addition, the outer surfaces of the roof rail extrusions shall be 100% continuously TIG welded to cast aluminum corner castings. The castings shall have internal mating flanges that extend horizontally inside the upper roof rail extrusion and vertically down the corner post extrusions.

FLOOR MEMBERS:

Floor structures shall be 6105-T5 aluminum, one-quarter (1/4) inch by 1.500 by 3.000 aluminum, architectural proprietary shape with bevels built into the extrusion die to allow for full weld penetration on the edge of the extrusions. The die must be designed so that the inside of the corner has the same thickness of aluminum as the remaining four sides.

FLOOR GUSSET PLATES:

The floor member to side wall fully welded gusset system shall be made of 5052-H32 aluminum plate, one quarter (1/4) inch thick by four (4) by four (4) inch and quarter (1/4) inch x six (6) inch x six (6) inch. A minimum of 12 gussets shall be located, dual gusset plates at each main cross member site.

FULL WIDTH CROSS MEMBERS:

The module floor shall provide core support for the side assemblies and shall incorporate a minimum of three (3) full body width floor members shall connect to and support the side wall assemblies. Each member shall be made of 6063-T6 aluminum. The front floor tube is to be a minimum of 3.000 x 1.500 x .250 thick 6105-T5 aluminum tube which is fully MIG welded into the front corner post at each side of the vehicle. On top of the tube is to be a minimum .188 thick 5052 aluminum front sill running full width of the body. One of the members located just forward and/or rear of the rear wheel housing shall be one-quarter (1/4) inch by 1.500 by 3.000 rectangular architectural box tubing. The last floor cross-member shall be a 1.625 x 2.188 x .250 6105-T5 aluminum tube on the rear wall which is fully MIG welded into the rear corner posts at each side of the



vehicle. This tube is butted up and welded to a 2.000 x 1.000 x .125 thick 6105-T5 tube which is also fully MIG welded to the rear corner post. A minimum of eight (8) total 6" gussets, (1/4) inch thick will be installed to reinforce two (2) at each cross member and sidewall tubes directly fore and aft of the axle.

TIGHT PATIENT CABIN:

The sub floor shall be shielded from moisture. A forty (40) mil thick aluminum sub sheet shall be sealed to the floor structure with silicone sealant. Additional aluminum plates shall be intermittent welded between compartments, wheel well liners, step wells and fuel filler housings. All of the areas shall be thoroughly sealed from one to the other, creating a sealed patient cabin from the outside. Extrusion hollows shall be filled with expandable foam sealant to prevent fumes and moisture from entering.

DOOR CONSTRUCTION

DOOR SKIN: No welded seams are allowed, only one piece formed corners. The door skin shall be .090 thick, 5052-H32 aluminum sheet formed on all four sides utilizing an ACF Multiflex Corner Former Model MF 25 to create a crevice free surface for best paint adhesion and corrosion resistance. The formed edges shall not have elongation cracks due to forming and shall maintain material thickness uniformly over the entire sheet. The formed edges uniformly round off seamless for better paint adhesion and aesthetic appeal that does not require cutting and welding in the corners.

DOOR FRAMING:

The door frame shall reinforce the perimeter of the skin pan. The extrusion shall incorporate a T-slot to receive an extruded, hollow, dual durometer closed cell UV protected TPV gaskets with relief holes for even compression for a proper and complete seal from the door to the door jamb. The gasket corners shall be welded without using adhesives for bonding. The door frame extrusion shall also add torsion resistance to the door assembly. The door jamb extrusion and frame extrusion shall be cut 45-degree on each corner. Each of the four corners shall incorporate a keyway and spline that is designed to drive into each corner and maintain a perfect 90-degree angle prior to welding. The door castings shall include gusset plates for additional support for the door construction. The door frame shall also incorporate a clearance way for UNF threaded blind fasteners for the door panels. The door panel shall not rest on the body of the blind fasteners.

FINAL DOOR ASSEMBLY:

The door skin shall be bonded to the frame assembly with an adhesive sealant in addition to intermittent welding. For entry doors: Additional, horizontal structure shall be added to maintain door skin flatness as well as penetration resistance in the event of a collision. The horizontal members are extruded J-channel, 0.150" thick. A minimum of two (2) horizontal members shall be welded in. A vertically oriented 0.150" thick formed hat-channel shall be welded to the webs of both horizontal channels for additional buckling resistance. Compartment doors shall have a reinforcement system of horizontal or horizontal/vertical structure added to maintain skin flatness and impact resistance.

ENTRY DOOR WINDOW(S) OPENINGS:

The entry door(s) shall incorporate recessed areas that are stamped into the outer door skin to allow for a flush window appearance and shall not protrude with a lip on the outer door skin of the modular body.



DOOR PANELS:

The inside entry door panels shall be made of (.080”) thick aluminum plate and shall be finished per these specifications later in this document. The center panel shall be removable for easy lock service/lubrication. The inside of the compartment door panels shall be made of (.080”) thick polished aluminum diamond plate. The edges of the door panel shall be recessed into the door frame extrusion. The panels shall be fastened to the door frame with stainless steel, #10-32 UNF machine screws threaded into aircraft quality blind fasteners. Each fastener shall have an internal tooth lock washer to preclude loosening.

DOOR JAMB:

The door jamb shall accommodate rigid fastening of compartment door hinges. The jamb shall include a hollow cell that shall conceal wiring for the non-mechanical door switch. The door jamb frame shall be cut 45-degree on each corner from the door edge corner, each of the four corners shall consist of a keyway and spline that is designed to drive into each corner and maintain a perfect 90- degree angle prior to welding. Additionally, the jamb shall be continuously MIG welded on the inside and the outside corners. *A seamless door jamb exterior is required to minimize corrosion - extruded type door jambs do not meet this specification. The skin shall completely conceal the door-jamb from view. "No Exterior Door Extrusions Allowed".*

HINGE:

All doors shall have stainless steel, continuous, piano hinge. The pin diameter shall be .250 and staked into place to prevent drifting out of the hinge leaf. The knuckle lengths shall be one inch. The hinge attachment bolts shall be one quarter inch diameter by one-inch-long stainless-steel Type TT (Thread Rolling Screws) hex head bolts. All tapped holes for hinge bolts shall be treated with an anticorrosion compound prior to installation of each hinge bolt. Thread cutting screws are not acceptable. Each hinge leaf shall have a Mylar insulation strip (3M Scotch No 8411) between the leaf and the Jamb/Door.

LATCHES:

The latches shall meet FMVSS 206. All latches shall be two-stage, rotary- type. The latches shall be through bolted to the door frame extrusion. All entry doors shall have two rotary latches per door. To assure uniform latch timing and functional door reliability, only straight, one-quarter (1/4) inch diameter rods shall connect the latches to the handle. All double hung compartment doors shall have two rotary latches per door.

NADER PINS:

All nader pins shall be headed to prevent the door(s) from opening under impact. They shall be hex headed Grade-8 fully adjustable with a 5/16” thick knurled stainless steel retainer plate to keep the nader pin from moving after adjusted. The opening in the door jamb extrusion shall be large enough to allow full adjustment with the nader pin washer covering the hole.

Bidder Complies YES _____ NO _____

BUILD TO SPEC VARIATION: The actual build unit may have a variation in actual sizing at any point of



up to 1/4" from quoted spec sizing. Where an actual size is deemed to be important as it impacts the fit of an article, it must be clearly noted with confirmation received from the manufacturer of ability to build.

MOUNTING

MOUNTING SYSTEM:

The body shall be 100% isolated from chassis vibrations. Welding and drilling additional holes in the flanges of the frame shall not be done anywhere between the axles and the outer most spring shackles. Twelve 1/4 thick out-rigger mounts shall be through bolted through the web (vertical wall of the frame) of the frame rail. New Holes drilled in the frame shall leave at least 1 of steel from the edge of the new hole and the edge an existing hole. Each mount shall utilize three grade-8, 5/8 diameter, flanged head bolts with flanged, locking nuts. Each mount shall accommodate a natural rubber vibration isolator and support for the body's mounting sill. All mounting sills shall be made of one-inch-thick by three-inch-wide solid aluminum flat bar. A grade L-9 seven sixteenth inch diameter by four-inch-long hex-head bolt shall be used to bolt the sill down at each isolator site.

Bidder Complies YES _____ NO _____

MODULE CONFIGURATION

MODULE LENGTH:

The module length shall be at least one hundred seventy inches. Bidder Complies

YES _____ NO _____

MODULE WIDTH:

The module width shall comply with current revision of Federal Specification KKK-A- 1822. The module shall be ninety-five inches wide, excluding lights and accessories.

Bidder Complies YES _____ NO _____

MODULE HEAD ROOM:

The module shall not be less than seventy-two inches of actual measured headroom. The measurement shall be taken from the patient compartment floor to the ceiling panels.

Bidder Complies YES _____ NO _____

DROP SKIRT:

Drop Skirt, six inches forward of rear wheels, Both sides

DOOR CHECK:

The compartment door(s) in excess of 13" pass through width shall be equipped with a door check (hold open) device. All vertically hinged doors in excess of 13" pass through width shall have a gas operated bi-



directional spring shock door check. Door check brackets shall be drilled and tapped through a minimum of 3/8" material to preclude coming loose.

Bidder Complies YES _____ NO _____

DOOR SWING:

The compartment door checks shall be installed to allow the door to open ninety degrees (90) from the fully closed position.

Bidder Complies YES _____ NO _____

CURBSIDE ENTRY DOOR LOCATION:

The curbside entry door to be moved forward to the bulkhead wall. The ALS/Right Stack cabinet to be moved to aft of the side entry door and will become a functional part of the head of the squad bench.

Bidder Complies YES _____ NO _____

COMPARTMENT CONSTRUCTION

MATERIALS:

Unless specified otherwise, all exterior compartment walls and backs shall be constructed of .100 polished aluminum diamond plate. All compartment floors shall be formed of .125 aluminum sheet. Compartments for generators, oxygen, and backboards will have .250 compartment floors. All compartment ceilings shall be formed of .090 aluminum sheet. The ceilings and floors shall form around the sides and back to provide an overlapping joint. The floor and ceiling surfaces shall be double action (DA) sanded to 180 grit. The floors and ceilings are bonded to the walls and back and intermittent welded on six (6) inch centers.

Bidder Complies YES _____ NO _____

DRAIN HOLES:

Drain holes shall be provided on the bottom of the compartments. Each hole shall be baffled to prevent splash water from entering the compartment.

Bidder Complies YES _____ NO _____

VENTILATION:

There shall be a hole in the compartment below floor line approximately 5-3/8" wide x 2- 9/32" tall that will accept a specially designed baffled vent. The baffles shall have a stainless-steel spring that allow for only one-way operation. They allow air to escape out of the compartment when the door is closed, but not for air to come back into the compartment to keep dirt and dust out of the compartment interior. Engineering shall determine the amount of these vents required by the volume of space in the compartment.

Bidder Complies YES _____ NO _____



CURBSIDE ACCESS DOOR:

The curbside access door shall be at least 76 13/16" high by 31" wide measured at the door jamb opening.

Bidder Complies YES _____ NO _____

JAMB PROTECTION

At the curbside, module entry door, a full width, formed, stainless steel jamb protection plate shall be provided to prevent heavy traffic from chipping the paint.

Bidder Complies YES _____ NO _____

DOOR CHECK:

The curbside entry door shall be equipped with a door check (hold open) device. All vertically hinged doors in excess of 13" pass through width shall have a gas operated bi-directional spring shock door check. Door check brackets shall be drilled and tapped through a minimum of 3/8" material to preclude coming loose.

Bidder Complies YES _____ NO _____

DOOR SWING:

The compartment door checks shall be installed to allow the door to open ninety degrees (90) from the fully closed position.

Bidder Complies YES _____ NO _____

CURBSIDE ACCESS DOOR LOCATION:

The module side entry door shall be located on the curbside of the module, just forward of the ALS cabinet to provide efficient egress into the module.

Bidder Complies YES _____ NO _____

STEP WELL: STREETSIDE FRONT MIDDLE COMPARTMENT

A curbside entry door shall feature a single step "step well" to assist in patient cabin egress. The step shall have a tread dimension of not less than 10 inches. The riser dimension shall not exceed twelve and one-half inches, measured from the step tread to the floor of the patient cabin. A right-angled trim, made of bright aluminum diamond plate, shall be formed over the flooring material and wrap around the 3-sided perimeter of the step well. Step well material shall be 0.100 thick, Polished aluminum diamond plate. The step well shall be illuminated. The step well shall meet or exceed Federal specification KKK-A-1822.

Bidder Complies YES _____ NO _____



STEP WELL ILLUMINATION: A 3" clear interior LED light shall illuminate the curbside step well per the current revision of Federal specification KKK-A-1822.

Bidder Complies YES _____ NO _____

STREETSIDE FRONT COMPARTMENT: This compartment shall be located in the left front corner of the modular body. The minimum compartment dimensions shall be 73" high x 30" wide x 17" deep. This compartment will hold a universal Oxygen bracket, Zico #QR-MV.

Bidder Complies YES _____ NO _____

VENTILATION:

There shall be three sets of six louver punches on the outside and inside door panel to properly ventilate the electrical components located in the above-mentioned compartment.

Bidder Complies YES _____ NO _____

DOG LEG:

The left front compartment shall have a dog leg for a stair chair storage forward of the oxygen storage.

Bidder Complies YES _____ NO _____

METAL SEATBELT STRAP:

Left front compartment shall have (1) metal seatbelt type strap to secure a stored stair chair forward of the oxygen storage.

Bidder Complies YES _____ NO _____

COMPARTMENT LIGHT:

LED strip lighting shall be mounted on each side and ceiling near the door jamb. A short piece shall be mounted over the Oxygen bottle and wired to the check-out timer.

Bidder Complies YES _____ NO _____

STREETSIDE FRONT MIDDLE COMPARTMENT:

This compartment is located adjacent and rearward to the left front compartment. The minimum compartment dimensions shall be 44" High x 39" Wide x 17" Deep.

Bidder Complies YES _____ NO _____

VENTILATION:

All compartments, made from aluminum sheet, shall have at least eight louvers of ventilation to the outside



below floor line. The oxygen cylinder and backboard compartments shall also be louvered through the inner and outer door panel up high with at least nine (9) square inches of free-vented area.

Bidder Complies YES _____ NO _____

ADJUSTABLE SHELF:

A standard duty aluminum fixed shelf shall be provided. The shelf shall be formed of .125 (1/8") thick aluminum with 2 inch upward turned lips on all four sides. This shelf will be in the upper section of the compartment and hold the electronics: Suction pump, inverter, and air compressor.

A standard duty aluminum adjustable shelf shall be provided. The shelf shall be formed of .125 (1/8") thick aluminum, with 2 inch upward turned lips on all four sides mounted on Unistrut infinitely adjustable, aluminum extruded, heavy duty shelf track. Incrementally adjustable, non-aluminum shelf track is not acceptable.

Bidder Complies YES _____ NO _____

SHELF BRACKET:

The above adjustable shelf shall include four (4) self-gusseted .157" thick shelf brackets that will allow for easy adjustment up and down for each shelf. Each bracket shall be secured to the shelf by carriage head bolts on the top of the shelf and hex head bolts to secure them to the shelf tracking material in the compartments. This will guard against shelf deformation in the compartments when the shelves are secured in place.

Bidder Complies YES _____ NO _____

COMPARTMENT LIGHT:

LED strip lighting shall be mounted on each side and ceiling near the door jamb.

Bidder Complies YES _____ NO _____

CONDUIT No 1:

An empty one- and one-half inch diameter conduit expressly designed to add wires after vehicle delivery by the end user or his/her authorized agent shall be supplied and installed. The conduit shall have semi-rigid, non-conductive liner that is free of inside ridges that can bind on the wire harness being pulled through the conduit. The outer jacket shall be a non-conductive, spiraled rigid coil designed to maintain the original shape of the liner, throughout the length of the conduit run.

Bidder Complies YES _____ NO _____

ORIGINATION POINT: The aforementioned conduit shall originate in the left front middle, exterior compartment.



TERMINATION POINT:

The aforementioned conduit shall terminate in the patient cabin behind the main action area control panel.

Bidder Complies YES _____ NO _____

CONDUIT No 2:

An empty one- and one-half inch diameter conduit expressly designed to add wires after vehicle delivery by the end user or his/her authorized agent shall be supplied and installed. The conduit shall have semi-rigid, non-conductive liner that is free of inside ridges that can bind on the wire harness being pulled through the conduit. The outer jacket shall be a non-conductive, spiraled rigid coil designed to maintain the original shape of the liner, throughout the length of the conduit run. A pull wire shall be installed into the conduit to aid the purchasing agency in future installation of equipment.

Bidder Complies YES _____ NO _____

ORIGINATION POINT:

The aforementioned conduit shall originate inside the main electrical cabinet.

TERMINATION POINT:

The aforementioned coaxial cable shall terminate in the cab behind the driver's seat. Bidder Complies

YES _____ NO _____

STREETSIDE REAR COMPARTMENT:

This compartment shall be located in the left rear corner of the body. The minimum compartment dimensions shall be "38" High x 34" Wide x 17" Deep.

ADJUSTABLE SHELF:

(2) Two standard duty aluminum adjustable shelves shall be provided. The shelves shall be formed of .125 (1/8") thick aluminum, with 2 inch upward turned lips on all four sides. The shelves shall be mounted on Unistrut infinitely adjustable, aluminum extruded, heavy duty shelf track. Incrementally adjustable, non-aluminum shelf track is not acceptable.

Bidder Complies YES _____ NO _____

COMPARTMENT LIGHT:

LED strip lighting shall be mounted on each side and ceiling near the door jamb.

Bidder Complies YES _____ NO _____



CURBSIDE REAR COMPARTMENT:

This compartment shall be located in the right rear corner of the body. The minimum compartment dimensions shall be 85" High x 19" Wide x 18.5" Deep. 61". This compartment shall have two dividers: one full height aluminum divider installed in the center and one half height aluminum divider rearward of center full height divider.

Bidder Complies YES _____ NO _____

CEILING VENTILATION:

Specified compartments shall have a hat channel at the ceiling level. The hat channel shall run to no closer than 1" from the compartment side walls to allow for air exchange. Hidden from view, shall be two to three, (4") holes above the hat channel to exhaust the compartment air when the door is closed to allow it to close with minimal effort.

Bidder Complies YES _____ NO _____

RETAINER STRAP:

One two-inch-wide webbed restraint strap shall be supplied in the compartment. The strap shall employ a metal buckle system with a push button release. The strap is to be fastened to the compartment walls with a two-inch footman's loop. The fastener is not to be fastened through the webbing material.

Bidder Complies YES _____ NO _____

COMPARTMENT LIGHT:

LED strip lighting shall be mounted on each side and ceiling near the door jamb.

Bidder Complies YES _____ NO _____

CURBSIDE REAR FORWARD COMPARTMENT:

This compartment shall be located just forward of the right rear compartment aft of the rear wheel opening. The minimum compartment dimensions shall be 22" High x 14" Wide x 17" Deep.

Bidder Complies YES _____ NO _____

COMPARTMENT LIGHT:

LED strip lighting shall be mounted on each side and ceiling near the door.

Bidder Complies YES _____ NO _____



CURBSIDE RIGHT FRONT COMPARTMENT:

This compartment shall be located in the right front of the module body, rearward of the curbside entry door. The minimum compartment dimensions shall be 88" High by 22" Wide. The compartment door shall provide direct outside access to the right front advanced life support equipment storage area and a 12" high stowage area, under floor level.

Bidder Complies YES NO _____

COMPARTMENT LIGHT:

LED strip lighting shall be mounted on each side and ceiling near the door.

Bidder Complies YES _____ NO _____

REAR ACCESS DOORS:

The rear of the module shall be equipped with double, hinged patient compartment access doors. The doors shall be centered on the body and align with the patient compartment aisle space.

REAR ACCESS DOOR JAMB:

At the rear access doors, a full width, formed, stainless steel jamb protection plate shall be provided to prevent the cot frames from chipping the paint. The stainless-steel protection package shall start from under the kick plate and follow the contour of the jamb extrusion, cover the end of the sub-floor and cover the last four inches of the vinyl floor covering.

Bidder Complies YES _____ NO _____

LOAD HEIGHT: Load height is defined as the vertical measurement from the level ground to the finished floor plane. The load height specified herein shall not exceed the current Federal specification KKK-A-1822.

Bidder Complies YES _____ NO _____

TALK THROUGH CAB TO MODULE WINDOW:

A 14" inch high by 19"-inch-wide access from the module to the cab shall be provided. Sliding polycarbonate doors shall close off the access window. The cab shall NOT be rigidly fastened to the modular body. A flexible, Accordion shaped, closed cell rubber bellows, custom made for the opening shall be provided to tie the cab to the module. One joint in the bellows is acceptable and shall be located on the bottom of the opening. The joint shall be completely vulcanized. The window provided shall meet or exceed current Federal specification KKK-A-1822.

Bidder Complies YES _____ NO _____



CAB ROOF SUPPORT:

There shall be a 3/16" thick by 3" wide extending from driver's side to passenger side on the underside of the cab roof above the headliner to prevent any oil canning noise that might be caused by wind against the front body wall and the cab roof.

Bidder Complies YES NO_____

FUEL FILLER AND HOUSING:

The filler neck supplied by the OEM shall be used. The filler neck shall be vented and be diameter indexed to accommodate a FUEL pump nozzle. The fuel filler neck shall be bolted to a cast aluminum fill housing. The filler housing shall be an open design with a bright polished mounting flange. The housing configuration and filler installation shall comply with the OEM Body Builders Layout Book. The fuel filler neck shall be grounded directly to the frame rail to prevent static electric charges from igniting the fuel vapors during refueling. The fuel filler cap shall be supplied by the OEM. The cap shall be attached to the filler housing with a lanyard. The filler cap shall incorporate an over-tighten protection device that ratchets when the preset cap torque is reached. The filler housing will have a black polyurethane type coating.

Bidder Complies YES_____NO_____

UREA FILLER AND HOUSING:

The filler neck shall be a Cast Products Inc. model FG5301-1. The filler neck shall be vented and be diameter indexed to accommodate the DEF nozzle. The fuel filler neck shall be bolted to the cast aluminum fill housing. The housing bezel shall be bright and polished. The housing configuration and filler installation shall comply with the OEM's Body Builders Layout Book. The filler cap shall be supplied by the OEM. The filler housing will have a black polyurethane type coating.

Bidder Complies YES_____NO_____

BODY PROTECTION AND BRIGHT WORK

WIRE/HOSE COVER:

The area between the back of the cab and the front of the module shall have a .100 aluminum diamond plate cover, attached to the frame rails, to protect any hoses and/ or wires routed in that location. The cover shall be mounted to close-off the area with a finished appearance.

Bidder Complies YES NO_____

FRAMING:

The rear step bumper shall exceed the current revision of KKK-A-1822. The bumper shall be framed in with 1/4 x 2 x 4 aluminum 6063-T6 rectangular tubing. The bumper shall be bolted directly to the chassis frame. In addition, the top of the bumper shall be mounted below the body skirt-line, so that minor collisions do not damage the body. The bumper will collapse under the body. For the stated reasons, there shall be no exceptions to this feature.



OUTER PONTOONS:

The outer bumper ends (pontoons) shall be covered in .100 polished aluminum diamond plate. The pontoons will have a black polyurethane type coating. The outer corners shall be angled 50 degrees. Each pontoon cover shall be through bolted to the bumper frame with stainless steel, pan-head, Phillips head, ¼-20 bolts and Nylock nuts.

DEPTH OF BUMPER:

The rear bumper shall protrude from the rear surface of the module body to the rearward most metal surface by at least nine- and one-half inches (9-1/2") and not more than ten inches (10"). black polyurethane type coating.

Bidder Complies YES _____ NO _____

CENTER STEP:

A flip-up step shall be provided to allow closer access to the patient cabin floor. The step shall be as wide as the rear access door jamb. The step shall have aggressive traction. A stainless-steel piano hinge shall have a staked in, ¼" diameter pin, one-inch knuckles and one Type-F ¼" through bolt every four inches. The rear bumper and center step shall have black poly urea coating.

Bidder Complies YES _____ NO _____

FENDERS:

The rear fender shall be black rubber. The fender shall be isolated and mounted to the wheel opening with thin membrane, double side tape. In addition to the tape, 100% nylon bolt and nuts shall hold the fender to the body.

Bidder Complies YES _____ NO _____

SKIRT RAILS:

The entire skirt-line of the body, forward and aft on the rear wheels shall be extruded "C" channel. Each skirt rail shall meet current Federal Specification KKK-A-1822. Each rail shall be chamfered 45 degrees at both ends. The rails shall be fastened through the bottom of the rail into the bottom of the modular body. The rails shall not cut into the paint. They shall be mounted through nylon isolators in such a manner that they are spaced off the body. The skirt rails shall be sprayed with black poly urea coating.

Bidder Complies YES _____ NO _____

REAR KICK PLATE:

The rear kick plate shall be made of 0.100-inch-thick aluminum diamond plate and run from corner post to corner post. The height shall be from the skirt-line of the body to the bottom door jamb under the rear access doors. The rear kickplate shall have a black poly urea coating.

Bidder Complies YES _____ NO _____



RECESSED TAG AREA:

The kick plate shall feature a centered and illuminated recessed area to mount a standard U.S. six-inch-high by twelve-inch-wide license plate. The recessed area must be located as specified below and aesthetically TIG Welded around the perimeter of the opening. Threaded inserts and bolts to install the tag shall be installed and provided.

Bidder Complies YES _____ NO _____

RECESSED TAG AREA LOCATION:

The tag area shall be centered on the kick plate. Shall be black polyurethane type coating.

Bidder Complies YES _____ NO _____

TAG LIGHT:

The tag area shall be LED illuminated with the park light circuit. Bidder

Complies YES _____ NO _____

BODY CORNER POST PROTECTION:

The lowest twenty-four inches (24") of the corner post extrusions shall be protected against stones and road debris. The corner post guards shall be formed of .080 thick polished aluminum diamond plate, contour fit to the corner post extrusions and riveted into place. A bead of silver colored silicone sealant shall be applied across the top edge of the guards. The bottom of edge of the guard shall be left unsealed to promote moisture drainage. Body corner posts shall have a black poly urea coating.

Bidder Complies YES _____ NO _____

FRONT OF BODY:

The front of the body shall have skirt-line protection plates made of .080 aluminum diamond plate. The corner posts shall have form fit diamond plate protection height matched to the frontal plates. The height of the protection is twenty-four inches up from the body skirt line. The front body diamond plate shall have a black poly urea coating

Bidder Complies YES _____ NO _____

REAR ACCESS DOOR CHECKS:

Rear access doors shall open at least 150 degrees. The door checks shall be 2-piece, heavy duty, cast aluminum, grabber type with gaskets. The door shall have a 1/2 round stock loop that plunges into a positive rubber/cast socket.

Bidder Complies YES _____ NO _____



RUNNING BOARDS:

Running boards (An auxiliary step) shall be constructed of .100 diamond plate with an aggressive traction "Grip strut" insert. The aggressive traction shall be part of the running board and not a welded in section. One running board shall be provided on each side of the cab. Built in diamond plate mud flaps shall keep front tire splash and road grime off the step. Running boards shall have a black poly urea coating.

Bidder Complies YES _____ NO _____

FRONT MUD FLAPS:

Mud flaps shall be mounted to the front fenders just behind the front tires. The mud flaps shall be 1/4" thick natural rubber material. Each mud flap shall be sandwiched between the wheel well liner and a torque distribution plate. The torque distribution plate shall be at least .100 thick aluminum plate. Each mud flap shall be through bolted to the fender with at least three (3) fasteners.

Bidder Complies YES _____ NO _____

REAR MUD FLAPS:

Mud flaps behind both sets of rear tires shall be supplied and installed. The mud flaps shall be 1/4" thick natural rubber material. Each mud flap shall be sandwiched between the wheel well liner and a torque distribution plate. The torque distribution plate shall be at least .100 thick aluminum plate. Each mud flap shall be through bolted to the wheel well liner with at least three (3) one-quarter inch (1/4") diameter stainless steel bolt.

Bidder Complies YES _____ NO _____

CORROSION:

The anti-electrolysis procedure for any holes that are drilled for application of materials is to be as follows, After the hole is drilled, the opening(s) is to be treated with Tactile 517 prior to installation of any fasteners to guard against any future corrosion.

Bidder Complies YES _____ NO _____

EXTERIOR FASTENERS:

All screw sites require a replaceable nylon insert for the fastener to thread into to isolate the dissimilar metals. Each hole shall be treated with an Electrolysis Corrosion Control compound (Tactile 517) prior to installation of the nylon inserts. All exterior screws shall be stainless steel.

Bidder Complies YES _____ NO _____



FRONT I.C.C. LIGHTS:

Clearance lights shall be provided per FMVSS 108. The lights shall illuminate the height of the vehicle, define the vehicle center line. Three (amber) lights shall be provided on the front of the module and be populated with at least two LED's. Black Flange

Bidder Complies YES NO

REAR I.C.C. LIGHTS:

Clearance lights shall be provided per FMVSS 108. The lights shall illuminate the height of the vehicle and define the vehicle centerline. Three red lights shall be provided on the rear of the module and be populated with at least two LED's. Black Flange

Bidder Complies YES NO

SIDE MARKER LIGHTS:

Side marker lights shall be Kinequip Model 112401RD (Red) and shall flash alternately with the rear turn lights. All lights shall be LED. Black Flange

Bidder Complies YES NO

STOP/TAILLIGHT:

The stop/taillight fixtures on the rear of the body shall be an M6 size, Light Emitting Diode to operate as both tail and stop modes and shall be red when illuminated. Black Flange

Bidder Complies YES NO

TURN SIGNAL LIGHT:

The turn signal light fixtures on the rear of the body shall be M6 size, Light Emitting Diode to operate as left and right turn signal lights and shall be amber arrow when illuminated. Black Flange

Bidder Complies YES NO

BACK UP SIGNAL LIGHT:

The back-up signal light fixtures on the rear of the body shall be M6 size, Light Emitting Diode to operate as left and right back up signal lights and shall be clear when illuminated. Black Flange

Bidder Complies YES NO

LIGHT HEAD FLANGE:

BLACK (Flange), on the above "M" Series light head(s). Bidder Complies

YES NO



REAR HVAC, 12V COMBO SYSTEM:

The ambulance shall be equipped with heating, ventilating, and air conditioning systems that operate using re-circulated air and ambient air and shall be capable of maintaining interior temperature within the established comfort zone of 68 degrees Fahrenheit to 78 degrees Fahrenheit while operating between 0 degrees and 95 degrees Fahrenheit ambient. Environmental system components shall be readily accessible for servicing at the installed location. The airflow selector switch shall provide a high, medium, and low setting. The switch shall be a common switch for both the heater and air conditioner. These environmental control switches shall be immediately accessible to the attendant while seated in the primary attendant seat located at the head of the primary patient.

An auxiliary air conditioner (A/C) shall be supplied and installed in the patient area of the modular body. The A/C unit shall be a self-contained unit with a cooling output capacity of 12,000 British Thermal Units (BTU). The unit shall be mounted per the A/C unit manufacturer's specifications. The A/C unit shall run on one hundred fifteen volts, alternating current at a frequency of sixty Hertz. Current draw shall not exceed fifteen Amperes, including the compressor and the fan motor set on HIGH speed. REFRIGERANT: The system shall operate on 24.5 ounces of R-22 Freon.

Bidder Complies YES _____ NO _____

THERMOSTAT:

The digital module control thermostat shall be located on a removable panel above the action wall. The system shall automatically maintain the set module temperature every time the vehicle is operated.

Bidder Complies YES _____ NO _____

A/C UNIT LOCATION:

Ceiling behind the attendant seat in an angled cabinet. A/C Unit will be a free flow non-ducted system.

Bidder Complies YES _____ NO _____

SECONDARY A/C CONDENSER:

There shall be a secondary a/c condenser installed on the exterior forward/upper wall of the module. The condenser shall have an aluminum housing, painted to match, with emergency lighting mounted to housing. The condensers shall be Hoseline 2050D. They shall provide 2948 CFM of air flow across the condenser cooling coils with four 12VDC fans and provide 50,000 BTU's of cooling for the 12V side. The evaporator blower shall have a brushless motor.

Bidder Complies YES _____ NO _____



CONDENSATION DRAIN PAN:

A condensation pan shall be provided to collect water condensation from the evaporator coil. The drain pan shall be formed from 1/8 ABS plastic sheet and shall be listed (tilted) toward the drain fitting. The Evaporator unit shall be mounted so that the weight of the coil, case and blower assembly does not rest on the pan. Additionally, the entire evaporator shall list toward the condensation drain fitting to enhance water flow to the drain hose. The drain hose shall be 1/2 I.D., collapse resistant and fiber reinforced poly-tubing. The hose shall be routed from the condensation pan to the street.

Bidder Complies YES _____ NO _____

HEATER HOSES:

Heater hoses for the cab shall remain O.E.M. 5/8 inside diameter, EPDM Nomex rubber hoses shall route from the O.E.M tie in point to the rear heater core.

Bidder Complies YES _____ NO _____

AIR CONDITIONING HOSES:

All A/C Hoses shall meet Society of Automotive Engineers (SAE) J-2064. The discharge (High side) hoses shall not be less than 5/16 inside diameter (Size 6). The suction (Low side) hoses shall not be less than 1/2 inside diameter (Size 10). All hoses shall be A.S.T.M. Type D, with a thermoplastic inner liner (Nylon) that is protected by two textile reinforced braided electrometric outer jacket. The hose shall be qualified for use with R-134A, R-404 and R-407. The hose specified herein shall be subjected to a battery of tests per A.S.T.M. D-380. The results shall be supplied by the hose manufacturer.

Bidder Complies YES _____ NO _____

RETURN AIR GRILLE:

Installed around the Heat/AC unit shall be a perforated 13-gauge steel grille. The grille shall allow 156 inches of return air flow to the Heat/AC unit. The grille shall provide complete access to the Heat/AC unit. The grille to have a black powder coat finish. There shall be two quarter turn locks supplied and installed on the grille. The locks shall have a black powder coated finish. Lock pawl activation shall be enabled with a round bitted key.

Bidder Complies YES _____ NO _____

CARBON FILTER:

The return air grille shall be supplied with a pre carbon filter that is designed to fit the slot within the grille. It shall be installed and shall not rattle. The filter shall be replaceable and/or cleanable by this department's fleet maintenance in the field.

Bidder Complies YES _____ NO _____



LINER PANELS:

The patient cabin head liner substrate material shall be a laminated panel of powder coated aluminum bonded to a center plastic panel. An upholstered center panel shall provide access to ceiling wiring and be covered in the same upholstery type as the seat and back rest pads found on the squad bench and/or CPR seat.

Bidder Complies YES _____ NO _____

PATIENT CABIN DOME LIGHTS:

The patient cabin shall have eight dual intensity, LED dome lights in the ceiling. The domes centers shall be aligned along two, four light banks. The left bank shall provide light directly over the patient; the right bank shall provide light directly over the aisle/squad bench. The dome lights and configuration shall meet current Federal Specifications KKK-A-1822.

Bidder Complies YES _ NO _____

TIMER CIRCUIT:

There shall be a solid-state timer circuit activated by a momentary switch mounted on the curbside door. The switch shall activate the solid-state device located on, or near the circuit board.

Bidder Complies YES _____ NO _____

LIGHTS POWERED BY TIMER:

The aforementioned timer shall power the street side (Left side) bank of dome lights on the high intensity setting. The duration of the light shall vary with the setting of the timer.

Bidder Complies YES _____ NO _____

IV HOOK No 1:

One chrome plated, surface mounted IV hook, with a spring-loaded retention gate, shall be supplied in the ceiling of the patient cabin. The hook shall feature an anti-swing strap next to the hook.

Bidder Complies YES _____ NO _____

LOCATION:

Located of the Primary patient, in proximity to the Head/Chest area of the patient.

Bidder Complies YES _____ NO _____



IV HOOK No 2:

One chrome plated, surface mounted IV hook, with a spring-loaded retention gate, shall be supplied in the ceiling of the patient cabin. The hook shall feature an anti-swing strap next to the hook.

Bidder Complies YES _____ NO _____

LOCATION:

Located of the Secondary patient, in the proximity to the Head/Chest area of the patient.

Bidder Complies YES _____ NO _____

CURB SIDE OVER HEAD ASSIST RAIL:

The rail shall exceed the current revision of current Federal specification KKK-A-1822. The rail shall be 1 ¼ diameter, 100% stainless steel with gray anti-microbial coating and 72 inches long. All rail fittings shall be TIG welded to the main rail.

Bidder Complies YES _____ NO _____

MODULE INSULATION:

The module insulation, except the under the floor shall consist of material having the following characteristics, 8mm thick nonabsorbent, reflective and shall have an air cell core. The air cell core shall consist of one layer of polyethylene bubble film that is sandwiched between one (1) layer of 99 percent pure aluminum foil and white colored polyethylene film. The insulation shall be installed with at least ½ air space from exterior skins, exposed to direct sun light. The insulation thermal rate testing shall be conducted in accordance with A.S.T.M. E84-89A, ANSI 2.5, NFPA 255, UBC 42-1, and U.L. 723. The walls shall not be less than R-15.0 down, R-7.31 Horizontally and R5.4 up. The insulation shall have a NFPA Class A and a UBC Class 1 fire rating with a flame spread index of 20 and a smoke developed index of 30. The application shall include a single layer of insulation on all four walls, doors, compartments, ceiling and floor.

Bidder Complies YES _____ NO _____

DOOR INSULATION UPGRADE:

Module entry doors shall have 0.1875-inch-thick mass loaded acoustical ethylene vinyl acetate material attached to the inside surface of the exterior skin to provide a noise reduction of 75%. There shall be 2-inch-thick moisture resistant hydrophobic micro porous polymeric substance adhered to the ethylene vinyl acetate material to provide added DB absorption and a minimum R rating of 11. The insulation shall be fitted tightly against the structural members to maximize R-value effectively. Gap spacing round each cell within the structure grid and the block foam shall not exceed 1/16". A layer of 0.250-inch-thick foil encapsulated micro-cellular closed-cell polyethylene with an R rating of 7.75. There shall be a minimum air gap of 0.5 inch between the inner most foil surface and the doors interior surface materials. Insulation shall not interfere with door latch hardware.

The total R value of the module entry doors must be greater than or equal to 12

Bidder Complies YES _____ NO _____



MODULE FLOOR INSULATION:

The floor shall have 0.5-inch-thick mass loaded acoustical (XPS) extruded polystyrene foam composite attached to the inside floor surface to provide a noise reduction of 75%. Patient compartment floor is now fully insulated for sound deadening and enhanced temperature control without increasing load height. The total R value of the floor must be greater than or equal to 4.5 to 5.0 per inch.

Bidder Complies YES _____ NO _____

ADDITIONAL INSULATION:

In addition to the standard reflective circumferential insulation, there shall be fiberglass bat insulation added to the walls and ceiling between the aluminum structural beams. It shall be cut into square or rectangular pieces to fit into the above locations.

Bidder Complies YES _____ NO _____

STEPWELL INSULATION PACKAGE:

The underside of the curbside step well shall be insulated between the structure with urethane froth insulation and then the underside shall be undercoated to protect the insulation from weather elements.

Bidder Complies YES _____ NO _____

PUBLIC ADDRESS (Visual) WARNING LIGHTS

WARNING LIGHT FLASHER:

There is not to be an external flasher unit. The LED warning lights shall each flash independently of each other. There shall be no preset flash pattern and it will not comply with the present revision of KKK-A-1822. This agency chooses to have this flash pattern as we feel that it is as effective as the required flash pattern incorporated within the verbiage of the present revision of KKK-A-1822.

Bidder Complies YES _____ NO _____



PRIMARY / SECONDARY SWITCH:

The warning light system shall be controlled with a switch(es) located in the cab console. The switch(es) shall allow for "Off" position, "Primary" position, and "Secondary" position. Each output of the switch shall be indicated with a small red lamp, integrated in the switch legend area. The switch shall have an engraved, illuminated legend that clearly defines the function of the switch.

Bidder Complies YES _____ NO _____

GRILLE LIGHTS

LIGHT HEADS:

A pair of M2 size LED Light heads shall be supplied in the aforementioned location. The light head shall feature Light Emitting Diodes. The light head shall comply with all photometric, chromaticity and physical requirements set forth in the current revision of Federal specification KKK. The lens shall feature a smooth outer surface designed to filter light frequency (Color) evenly over the area of the entire light head. A certificate of Compliance shall be made available to the agency upon request.

Light: M2, LED, RED/BLUE LED/CLEAR Lens, Programmable with black flange.

FLASH PATTERN:

The programmable split color light shall have each independent color flasher programmed to a separate flash pattern by the up-fitter. The flash pattern number shall be confirmed by the agency at the pre-construct meeting. The individual sections of the light are not synched to any other light portion.

Bidder Complies YES _____ NO _____

INTERSECTION LIGHTS

LIGHT HEADS:

A pair of M4 size LED Light heads shall be supplied in the aforementioned location. The light head shall feature Light Emitting Diodes. The light head shall comply with all photometric, chromaticity and physical requirements set forth in the current revision of Federal specification KKK. The lens shall feature a smooth outer surface designed to filter light frequency (Color) evenly over the area of the entire light head. A certificate of Compliance shall be made available to the agency upon request. Black Flanges.

Bidder Complies YES _____ NO _____

LIGHT HEAD HOUSING:

The intersection light shall have a contoured housing to fit the OEM fender. Black Flanges.



INTERSECTION LIGHTS:

There shall be provided M4 size RED/BLUE LED, Clear Lens warning lights with programmable flash patterns.

Bidder Complies YES_____NO_____

CENTER FRONT BODY LIGHT

LIGHT HEADS:

A M9 size LED Light head shall be supplied in the aforementioned location. The light head shall feature Light Emitting Diodes. The light head shall comply with all photometric, chromaticity and physical requirements set forth in the current revision of Federal specification KKK. The lens shall feature a smooth outer surface designed to filter light frequency (Color) evenly over the area of the entire light head. A certificate of Compliance shall be made available to the agency upon request.

Bidder Complies YES_____NO_____

LIGHT HEAD FLANGE:

BLACK (Flange), on the above "M" Series light head(s). Bidder Complies YES

_____NO_____

Light: M9, LED, WHITE LED/CLEAR Lens, Programmable

The above LED light(s) shall be programmable to flash without an external

flasher. Bidder Complies YES_____NO__

OUTER FRONT BODY LIGHTS

LIGHT HEADS:

A pair of M9 size LED Light heads shall be supplied in the aforementioned location. The light head shall feature Light Emitting Diodes. The light head shall comply with all photometric, chromaticity and physical requirements set forth in the current revision of Federal specification KKK. The lens shall feature a smooth outer surface designed to filter light frequency (Color) evenly over the area of the entire light head. A certificate of Compliance shall be made available to the agency upon request.

Bidder Complies YES_____NO_____

LIGHT HEAD FLANGE:

BLACK (Flange), on the above "M" Series light head(s). Bidder Complies

YES_____NO_____



Light:

M9, LED, RED/BLUE LED/CLEAR Lens, Programmable

The above LED light(s) shall be programmable to flash without an external

flasher. Bidder Complies YES_____ NO_

INNER FRONT BODY LIGHTS

LIGHT HEADS:

(4) Four additional M9 size LED Light heads shall be supplied in the aforementioned location. Light heads to be RED/BLUE with clear lens. The light head shall feature Light Emitting Diodes. The light head shall comply with all photometric, chromaticity and physical requirements set forth in the current revision of Federal specification KKK. The lens shall feature a smooth outer surface designed to filter light frequency (Color) evenly over the area of the entire light head. A certificate of Compliance shall be made available to the agency upon request.

Bidder Complies YES_____ NO_____

LIGHT HEAD FLANGE:

BLACK (Flange), on the above "M" Series light head(s). Bidder Complies YES____

NO_____

Light:

M9, LED, RED/BLUE LED/CLEAR Lens, Programmable

The above LED light(s) shall be programmable to flash without an external

flasher. Bidder Complies YES_____ NO_

UPPER SIDE BODY LIGHTS

LIGHT HEADS:

Two pairs of M9 size LED Light heads shall be supplied in the aforementioned location. The light head shall feature Light Emitting Diodes. The light head shall comply with all photometric, chromaticity and physical requirements set forth in the current revision of Federal specification KKK. The lens shall feature smooth outer surface designed to filter light frequency (Color) evenly over the area of the entire light head. A certificate of Compliance shall be made available to the agency upon request.

Bidder Complies YES_____NO_____



LIGHT HEAD FLANGE:

BLACK (Flange), on the above "M" Series light head(s). Bidder Complies

YES _____ NO _____

WARNING LIGHT:

There shall be installed a M9 size Red/Blue LED light with Clear lens and programmable flash functions.

Bidder Complies YES _____ NO _____

The above LED light(s) shall be programmable to flash without an external

flasher. Bidder Complies YES _____ NO _____

ADDITIONAL INTERSECTION LIGHTS:

There shall be a M7 size Red/Blue LED lights on the side of the module at approximately belt-line height, above the rear wheels.

Bidder Complies YES _____ NO _____

LIGHT HEAD FLANGE:

BLACK (Flange), on the above "M" Series light head.

Bidder Complies YES _____ NO _____

REAR OUTER BODY LIGHTS

LIGHT HEADS:

A pair of M9 size LED Light heads shall be supplied in the aforementioned location. The light head shall feature Light Emitting Diodes. The light head shall comply with all photometric, chromaticity and physical requirements set forth in the current revision of Federal specification KKK. The lens shall feature a smooth outer surface designed to filter light frequency (Color) evenly over the area of the entire light head.

A certificate of Compliance shall be made available to the agency upon request.

Bidder Complies YES _____ NO _____

LIGHT HEAD FLANGE:

BLACK (Flange), on the above "M" Series light head(s).

Bidder Complies YES _____ NO _____



WARNING LIGHT:

There shall be installed a Whelen M9 size Red/Blue LED light with Clear lens and programmable flash functions.

Bidder Complies YES_____ NO_____

The above LED light(s) shall be programmable to flash without an external flasher.

Bidder Complies YES_____ NO_____

ADDITIONAL REAR BODY LIGHTS

LIGHT HEADS:

A pair of M9 size LED Light heads shall be supplied in the aforementioned location. Bidder Complies

YES_____ NO_____

LIGHT HEAD FLANGE:

BLACK (Flange), on the above "M" Series light head(s). Bidder Complies YES_____

NO_____

LOCATION:

On the rear of the module, aligned with each upper window in the access doors. The light shall flash through the window when the doors are opened.

Bidder Complies YES_____ NO_____

WARNING LIGHT:

There shall be installed a M9 size RED/BLUE LED light with Clear lens and programmable flash functions

Bidder Complies YES_____ NO_____

The above LED light(s) shall be programmable to flash without an external flasher.

Bidder Complies YES_____ NO_____

CENTER REAR BODY LIGHTS

LIGHT HEADS:

A M9 size LED Light heads shall be supplied in the aforementioned location. The light head shall feature Light Emitting Diodes. The light head shall comply with all photometric, chromaticity and physical requirements set forth in the current revision of Federal specification KKK. The lens shall feature a smooth



outer surface designed to filter light frequency (Color) evenly over the area of the entire light head. A certificate of Compliance shall be made available to the agency upon request.

Bidder Complies YES _____ NO _____

LIGHT HEAD FLANGE:

BLACK (Flange), on the above "M" Series light head(s). Bidder Complies

YES _____ NO _____

Light:

Whelen M6, LED, AMBER LED/CLEAR Lens, Programmable

The above LED light(s) shall be programmable to flash without an external

flasher. Bidder Complies YES _____ NO _____

PROGRAM SWITCH WIRING:

The emergency lighting harness shall include cabling for light program changing from the circuit board. Each light head location shall have a cable routed from the light head location to the circuit board area. The cable shall be minimum shielded, 18 AWG, cable with a polyvinyl chloride (PVC) jacket. All aforementioned cables shall have a six-inch service loop on each end to allow for future connections.

Bidder Complies YES _____ NO _____

ELECTRICAL SYSTEM 12 Volt - General

MODULE GROUNDING: A minimum of (2) two braided ground straps shall be through bolted to the chassis frame and the floor structure of the modular body. The bolts shall be at least 3/8 diameter. A flat washer shall be provided under the head of the bolt, over the strap lug. Additionally, an internal tooth lock washer shall preclude loosening. Conventional stranded copper cables are not acceptable because they do not suppress RFI and does not meet SAE J551.

Bidder Complies YES _____ NO _____



GENERAL GROUNDS:

To comply with current Federal specification KKK-A-1822 plus enhance ground quality and reduce trouble shooting time, all devices wired within the ambulance conversion shall be centrally grounded. Each device shall have a separate ground wire routed to a central buss bar then grounded via fine strand cable to the module body. Local grounds are acceptable only when the device is drawing at or less than 100 milliamps (0.1 amps).

Bidder Complies YES_____ NO_____

12 VOLT WIRE:

All wires within the ambulance harnesses shall meet current Federal specification KKK-A-1822. All wire insulation shall be GXL cross-linked polyethylene. Permanent wire identification and wire function shall be printed on 4 centers along the full length of the wire. Wire conductors shall be stranded copper.

Bidder Complies YES _ NO_____

WIRE PROTECTION:

All wire within the conversion shall be protected and run in a split convoluted loom with a melting temperature of 300 degrees Fahrenheit. All wire harnesses shall be clamped and routed to eliminate the possibility of damage due to cut/chaffed wire. Grommets made of rubber or plastic shall be used where harnesses pass through metal or wood. Large holes and irregularly shaped wire passages shall use automotive edge trim to protect the wire conduit/loom. Wire harnesses shall be neatly clamped into protective routing areas away from heat sources, unfriendly edges or moving devices.

Bidder Complies YES_____ NO_____

TWO BATTERY SYSTEM:

The ambulance conversion and chassis shall run with two maintenance free twelve volt batteries as specified below.

BATTERY LOCATION:

Both batteries shall be located under the OEM hood in the engine compartment. Bidder Complies

YES_____ NO_____

BATTERY BRAND:

Both batteries shall be the OEM brand, same model, and type. Each battery shall be rated at a minimum OEM rating. The batteries shall be warranted by the OEM manufacturer for at least three years (thirty-six months) from the date of delivery to the agency.

Bidder Complies YES_____ NO_____



BATTERY SWITCH:

A conversion disconnect switch shall be supplied to remove positive polarity from the ambulance conversion circuits. Constant battery power shall be supplied for device memories. None of the chassis' functions shall be effected by this switch per Fords Qualified Vehicle Modifiers program, bulletin No 63. The switch shall be a Cole Hersee Model M2484-16 with a legend bezel that defines the ON and OFF position. An indicator light shall illuminate on the cab console panel.

Bidder Complies YES _____ NO _____

POWER MODULE DOOR LOCKS:

Each compartment and/or entry doors listed below shall Lock or Unlock with a single depression of a momentary switch. Each door shall be fitted with a bidirectional, momentary electric solenoid designed to operate a mechanical rod in a linear fashion. The rod shall mechanically interface with the door lock mechanism inside the door. All rod connections shall be designed for high cycle operation without mechanical disconnection. The battery compartment shall NOT have the power lock/unlock feature. This compartment shall remain key operated.

Bidder Complies YES _____ NO _____

DOOR LOCK SWITCH:

The aforementioned door lock(s), shall be wired to activate with the OEM cab door locks and their switches in the cab.

Bidder Complies YES _____ NO _____

OEM KEY FOB OPTION:

The aforementioned door lock(s), shall be wired to activate with the OEM cab door locks and their switches in the cab as well as the OEM remote key fob activator.

Bidder Complies YES _____ NO _____

DOOR LOCK SWITCHES:

The module entry doors shall have internal integrated electric door lock activation switches mounted on door.

Bidder Complies YES _____ NO _____

POWER DOORLOCK KEYPAD:

A weatherproof keypad shall be installed on the front wall of the module on driver side, at chassis window level.

Bidder Complies YES _____ NO _____



CAMERA SYSTEM:

The vehicle shall include a single camera backup monitoring system. The system shall be connected to the OEM screen in the dash. The screen shall be connected to a camera mounted on the rear of the ambulance body to allow the driver to view as they are backing up. Unless otherwise specified, the camera shall be mounted over the rear doors as close to the centerline of the vehicle as possible.

Bidder Complies YES _____ NO _____

CIRCUIT BOARD:

The single relay control board is a fully integrated relay control board designed and built to IPC Class 3* guidelines. The VF4 style socket relay is rated at 20A at 24 VDC with built-in on-board diode suppression. Three status indicators for Blown Fuse, Coil Power and Load allow for intuitive operation and troubleshooting. Also included is a medium sized ATO blade style fuse / circuit breaker holder that is rated for 20A. Wiring connections are made via a WAGO Cage Clamp removable lockable connector, which provides a secure, vibration proof and corrosion resistant wire termination. Installation time is reduced by as much as 75%. All of these features are mounted in a 2"x2" DIN Rail mountable package. Clearly, the Single Relay Control Board is a best-in-class solution for Emergency Vehicle relay applications.

Bidder Complies YES _____ NO _____

CIRCUIT BREAKERS:

All conversion-related circuits shall be protected with manual reset blade breakers. The value of the breaker for each circuit shall not exceed 75% of the rated capacity of the weakest component in the circuit.

Bidder Complies YES _____ NO _____

CAB CONSOLE:

An ergonomically designed console made from aluminum, shall be contour matched to the cab floor. The console shall be a parallel wall design with a twelve- and one-half inch over all width. End panels and center console bulkhead panels shall add rigidity and square to the console. The substrate shall be laminated per the following finish specification.

Bidder Complies YES _____ NO _____

SWITCH PANEL, CAB CONSOLE:

A switch panel made from 3/16 thick, translucent, acrylic sheet. The acrylic material shall evenly disperse label, indicator illumination. The Sheet shall be coated with a black colored, rigid plastic film. A CNC router shall engrave, permanent switch legends, switch holes, meter holes, and indicator legends. The switches shall be organized in two rows. The top row shall start with an Emergency Master, followed by all of the emergency related switches. The bottom row shall start with a Master Switch, followed by all of the non-emergency related switches.

Bidder Complies YES _____ NO _____



MASTER SWITCH:

The patient area master switch shall be located in the cab switch console. Bidder Complies

YES _____ NO _____

VOLTMETER:

The charging system voltage condition shall be indicated through a conventional two-inch diameter, analog type gauge. The voltmeter shall be wired through the ignition switch and indicate system voltage ranging from eight to sixteen volts, direct current.

Bidder Complies YES _____ NO _____

COMPARTMENT AJAR INDICATOR LIGHT:

A back lighted "Compt Open" light shall be engraved in the cab console's main switch panel. This light color shall be AMBER. The light shall meet current Federal Specification KKK-A-1822.

Bidder Complies YES _____ NO _____

INDICATOR LIGHT FUNCTION:

The door ajar indicator light shall flash when two conditions are met:

- 1) The main conversion power switch is turned to the ON position.
- 2) Any compartment or entry door is open.

The door ajar light shall come ON with a door that is not COMPLETELY latched.

Bidder Complies YES _____ NO _____

BATTERY POWER "ON" INDICATOR LIGHT:

An indicator light, labeled "Amb Pwr" shall be engraved in the cab console's main switch panel. The light color shall be GREEN. The light shall meet current Federal Specification KKK-A-1822.

Bidder Complies YES _____ NO _____

INDICATOR LIGHT FUNCTION:

The "Amb Pwr" indicator light shall burn steadily when the main conversion power switch is turned to the ON position.

Bidder Complies YES _____ NO _____



DOOR AJAR INDICATOR LIGHT:

A back lighted "Door Ajar" light shall be engraved in the cab console's main switch panel. This light color shall be RED. The light shall meet current Federal Specification KKK-A-1822.

Bidder Complies YES _____ NO _____

SWITCHPANEL ILLUMINATION:

Illumination of the switch panels shall be provided by LED strips attached to the underside of the switch panels. The strips shall be powered by 12volt DC.

Bidder Complies YES _____ NO _____

AUXILIARY CAB CONSOLE:

A ergonomically designed extension console shall be contour matched to the Main ambulance conversion console. The console shall be a tapered design with a fourteen- and one-half inch width at the front of the console and a twelve-inch width at the rear of the console. The height shall not exceed the height of the engine cover console measured at the rear. The length of the console, measured at the center, shall be at least twenty-one inches.

Bidder Complies YES _____ NO _____

DRINK HOLDERS:

The aforementioned extension console shall feature two drink holders, large enough to accommodate 44-ounce paper cups. The drink holders shall be recessed into the console with a one-piece, self-rimming trim rings. The console finish and the drink hole recessed areas shall be waterproof, due to cup condensation. Would prefer Deep cup holders that can hold a 40 OZ tumbler without it tipping over onto the console like the last previous 3 cup holders styles

Bidder Complies YES _____ NO _____

The Drink Holder shall be located at the Front of the Add On Console.

Bidder Complies YES _____ NO _____

NOTEBOOK SLOT:

The aforementioned extension console shall feature a four inch by full width slot specifically designed to hold notebooks and/or clipboards. The inside finish of the slot shall be of the same material as the outside laminate. The slot shall be located in the rearward most end of the extension console.

Bidder Complies YES _____ NO _____

The aforementioned "notebook slot" shall feature two removable dividers that are evenly spaced in the slot.



Extruded C-channels fastened to the sides shall be employed to secure the dividers into place. The divider will be placed so that there is one 4" wide compartment.

Bidder Complies YES _____ NO _____

CAB CONSOLE FINISH:

The console body shall be finished with a 20 mil Easy Grip film. The Easy Grip shall be a self-adhesive as well as bonded to the substrate with high bond contact adhesive. All joints shall be inconspicuous and bonded along the edges.

Bidder Complies YES _____ NO _____

CAB CONSOLE FINISH:

The console body shall be finished with a 20 mil Easy Grip film. The Easy Grip shall be a self-adhesive as well as bonded to the substrate with high bond contact adhesive. All joints shall be inconspicuous and bonded along the edges.

Bidder Complies YES _____ NO _____

BACK UP ALARM:

The apparatus shall include a 97 to 107 decibel back up alarm, activated by shifting into reverse.

Bidder Complies YES _____ NO _____

CUT-OFF SWITCH, BACK-UP ALARM:

As a safety feature, there shall **NOT** be a cut-off switch for the backup alarm.

Bidder Complies YES _____ NO _____

GROUND STRAPS:

Four (4) 7/8" wide by 1/8" thick, fine strand, woven straps shall provide a ground path from the module body to the chassis frame. Woven straps filter out RFI noise originating from alternators, strobe power supplies and other devices, that may find their way into intercom, stereo and two-way communication radios. The end of the ground straps shall be through bolted with 3/8" diameter, grade 5 or 8, hex head bolts and lock nuts. Each connection site shall be cleaned to the bare metal prior to fastening the strap. The connections shall have a dielectric anti corrosion spray applied.

Bidder Complies YES _____ NO _____



12 VOLT POWER INVERTER:

A highly reliable Vanner 1050CUL electronic power conversion unit that utilizes MOSFET power semiconductors and a microprocessor controller shall be supplied, installed, and wired to the outlets specified herein. A Built in 20A automatic transfer switch shall transfer all loads from the inverter to the shoreline, when the shoreline cord is plugged into 125 vac shoreline power. The device shall convert 12-volt DC battery power into 1,050 watts of precisely regulated modified sine wave 125-volt AC power. The device shall hold output power between 114 volts and 126 volts AT a frequency of 59.9 to 60.1 Hertz. The device shall not consume more than 105 amperes at 12-volts direct current (DC). The device shall be certified by Underwriters Laboratories to the present revision of the Federal Specification KKK-A-1822. The inverter shall be in the streetside intermediate compartment, mounted on the ceiling with a metal mesh protection cage.

Bidder Complies YES _____ NO _____

POWER SOURCE FOR PORTABLE EQUIPMENT No 1:

Power sources are located and included with a purchased inverter.

Bidder Complies YES _____ NO _____

LOCATIONS:

The power sources shall be located: (1) in cab console, and (1) behind the A/A panel. Bidder

Complies YES _____ NO _____

POWER SOURCE:

The aforementioned power provision shall be fed off of the output of the ignition switch or when the battery charger/conditioner is connected to the shoreline.

BATTERY CHARGER/CONDITIONER:

When the system is connected to shore/utility power, the battery charger (built into the aforementioned inverter) will automatically charge the batteries, then keep them fully charged. The system's microprocessor controls the charging sequence, starting with the high charger (55 Amp) mode. When the batteries are fully charged, it switches to the ready/maintenance mode to keep the battery "topped up". The battery charger shall be designed to charge either lead acid flooded (wet) or gel type batteries.

Bidder Complies YES _____ NO _____

BUILT-IN BATTERY CHARGER:

The aforementioned built-in battery charger shall be wired to the vehicle batteries to allow charging/conditioning when the shoreline is energized.

Bidder Complies YES _____ NO _____



The power inverter shall reside in the Curbside front middle compartment.

Bidder Complies YES _____ NO _____

LOW VOLTAGE INDICATOR:

There will be an amber indicator light located in the cab console to illuminate if the vehicle voltage drops below 11.8 volts DC. If the voltage remains under 11.8 volts DC in excess of 120 seconds, there shall be a warning buzzer in addition to the light.

Bidder Complies YES _____ NO _____

COMMUNICATIONS RADIO(S) RELATED RADIO

POWER

POWER SOURCE FOR COMMUNICATION RADIO(S) No 1:

Positive and Negative polarity ten-gauge wires shall be supplied and installed for subsequent installation of communications radio(s). The wires shall be barreled off and protected by a thirty (30) ampere automatic reset circuit breaker.

Bidder Complies YES _____ NO _____

POWER SOURCE:

The power provision shall be fed off the output of the conversion main power (Battery) switch.

Bidder Complies YES _____ NO _____

LOCATION:

The power source shall be located behind the passenger's seat, in the cab. Bidder

Complies YES _____ NO _____

POWER SOURCE FOR COMMUNICATION RADIO(S) No 2:

Positive and Negative polarity ten-gauge wires shall be supplied and installed for subsequent installation of communications radio(s). The wires shall be barreled off and protected by a thirty (30) ampere automatic reset circuit breaker.

Bidder Complies YES _____ NO _____



POWER SOURCE:

The power provision shall be fed off the output of the conversion main power (Battery) switch.

Bidder Complies YES _____ NO _____

LOCATION:

The power source shall be located behind the Action area control panel in the patient cabin. Bidder

Complies YES _____ NO _____

ANTENNA LEADS

COMMUNICATIONS RADIO ANTENNA PRE-COAX No 1:

This coaxial cable shall be RG58-U type. Leave an 18-service loop at the mod roof and a 36 tail at the interior termination point. A tag shall specify the other termination point for each coax provided.

Bidder Complies YES _____ NO _____

ORIGINATION POINT:

The Coaxial cable shall originate on the module roof. The port location shall be centered side to side and approximately 36" back from the front edge of the module roof.

TERMINATION POINT:

The Coaxial cable shall terminate in the cab / drivers' cabin behind the passenger seat.

Bidder Complies YES _____ NO _____

125V SHORELINE AND OUTLETS

SHORELINE INLET No 1:

The primary 125 Volt shoreline inlet, rated at 20 Amperes shall be supplied. The plug style shall be a straight blade (NEMA 5-20P) style with a U-shaped ground. The inlet shall automatically eject the shoreline connector when the vehicle ignition switch is placed in the START position. The shoreline inlet shall employ a novel internal switch that closes and opens the 125 Volt circuit after the mating connector is inserted and before the connector is removed to eliminate arcing at the connector contacts. This will prolong the life of the inlet and the shoreline connector. The inlet shall be protected with a weatherproof cover.

Bidder Complies YES _____ NO _____



SHORELINE 1 LOCATION:

Shorelines will be located on the back of the Patient Compartment box on the Driver's side approximately 48" of the ground when not in the kneeling setting.

Bidder Complies YES _____ NO _____

SHORELINE COVER:

The shoreline inlet shall be protected with a white weatherproof cover.

Bidder Complies YES _____ NO _____

SHORELINE EJECT TIMER:

The shoreline timer shall be an Inpower VCM-05-01SF to allow the auto eject to be wired to the ignition switch ILO splicing into the OEM starter circuit

Bidder Complies YES _____ NO _____

SHORELINE EJECT TIMER:

The shoreline timer shall be an Inpower VCM-05-01SF to allow the auto eject to be wired to the ignition switch ILO splicing into the OEM starter circuit

Bidder Complies YES _____ NO _____

125 VAC OUTLETS

125 VAC OUTLET No. 1:

The following outlets shall be UL listed, 125 Volt, Hospital grade, Straight blade NEMA 5-15R outlets. Each outlet shall be installed in a UL listed, recessed, fiberglass back box with a minimum of one- and three-quarter inch of box depth. The outlet cover shall be stainless steel. The outlet must be grounded and protected by a GFI (Ground Fault Interrupted) Breaker. Each outlet body must illuminate when power is applied to the outlet. Each Outlet shall be clearly labeled with a permanent RED colored decal defining the outlet voltage.

Bidder Complies YES _____ NO _____

OUTLET LOCATION:

This 125 Volt outlet shall be located in the patient cabin's main "Action Area", with location as shown on the approval drawings.



125 VAC OUTLET No. 2:

OUTLET LOCATION:

This 125 Volt outlet shall be located inside of the right front ALS Cabinet. The outlet shall be mounted on the left wall of the cabinet (related to inside access) in the upper cabinet. The location of the outlet shall be defined in the proposal drawings.

Bidder Complies YES _____ NO _____

125 VAC OUTLET No. 3:

OUTLET LOCATION:

This 125 Volt outlet shall be located inside of the right front ALS Cabinet. The outlet shall be mounted on the left wall of the cabinet (related to inside access) in the lower cabinet. The location of the outlet shall be defined in the proposal drawings.

Bidder Complies YES _____ NO _____

125 VAC OUTLET No. 4:

OUTLET LOCATION: This 125 Volt outlet shall be located in the patient cabin's telemetry area that is located just aft of the street side CPR side seat. The outlet shall be mounted on the back wall so that the depth of the back box does not protrude into adjacent cabinets. The location of the outlet shall be defined in the proposal

drawings. Bidder Complies YES _____ NO _____

125 VAC OUTLET No. 5:

OUTLET LOCATION: This 125 Volt outlet shall be located in the face of the Squad Bench on the curb side of the patient cabin. The location of the outlet shall be defined in the proposal drawings.

Bidder Complies YES _____ NO _____

125 VAC OUTLET No. 6:

OUTLET LOCATION: This 125 Volt outlet shall be located in the front bulkhead cabinet above the oxygen cylinder holders for flashlights. The location of the outlet shall be defined in the proposal drawings.

Bidder Complies YES _____ NO _____

INTERIOR 12 Volt Direct Current (DC) OUTLETS

12 VOLT OUTLET No 1, 2 and 5:

This outlet shall be a 12-volt, direct current, 20 Ampere, automotive "cigar" lighter size commercial outlet.



This outlet shall be located and wired as specified below. The outlet shall be separately protected and shall be electrically isolated from other electrical functions on the vehicle. This outlet shall be wired per current Federal specification KKK-A-1822.

Bidder Complies YES _____ NO _____

OUTLET LOCATION:

This 12 Volt outlet shall be located in the patient cabin's main "Action Area", on the back wall. #5 shall be located in designated area front bulkhead cut out.

POWER SOURCE:

The input for the outlet shall be wired to the output of the battery switch.

Bidder Complies YES _____ NO _____

12 VOLT OUTLET No 3 and 4:

This outlet shall be a 12-volt, dual port USB outlet with a 2.4amp output in each port.

Bidder Complies YES _____ NO _____

OUTLET LOCATIONS: No. 3 shall be located in main 'Action Area', on the back wall. No. 4 shall be located in the chassis console.

ELECTRONIC SIREN: A 295HFSC9 equivalent siren hardware shall consist of a combination control head with integrated amplifier. The mono or dual sound output shall include 8-programmable operating profiles and include a removable microphone. The siren control head shall feature a rocker type power switch, rotary function/Mode switch, a Manual momentary button switch and a microphone volume control potentiometer.

Bidder Complies YES _____ NO _____

SIREN OR HORN SELECTOR SWITCH: The O.E.M. horn ring shall control the O.E.M. electric horn and the siren's manual momentary input controls. A switch shall connect the horn ring to either the O.E.M. HORN or to the SIREN. The switch shall be located in the cab console's switch panel. The switch legend, that clearly defines the switch function shall be engraved in the switch panel. The legend shall be illuminated when the head light switch is on.

Bidder Complies YES _____ NO _____



SIREN SPEAKERS: The speakers shall each have a 100-watt driver and shall emit through an horn body located directly behind the O.E.M. fog light location in the bumper area, one on left side and one on right side. The siren and speakers shall meet or exceed current KKK-A-1822 Specifications. Poly urea black coated.

Bidder Complies YES _____ NO _____

AIR HORN SYSTEM: The apparatus shall be supplied with an authoritative-sounding air horn system that is loud enough to overwhelm almost every usual audible distraction. The air horns shall, when enabled, emit a loud (138 decibel) signal with tremendous power for the duration of the users' depression of the Activation switch. The system shall contain two horns of UNEQUAL length to cover a wider frequency range. Airhorns shall be mounted through the front bumper area.

AIR HORN ACTIVATION: The air horns shall be activated through a momentary switch located in the console switch panel. Momentary switch to be labeled as 'AIRHORN'.

Bidder Complies YES _____ NO _____

AIR HORN SUPPLY TANK: There shall be a air horn supply tank to store the air that is generated by the compressor to supply the specified horns. This tank that shall be determined by engineering and the air horn manufacturer shall be secured to the chassis frame rails.

AIR HORN ACTIVATION REQUIREMENTS: The Emergency Master switch shall be activated for the air horns to be active.

Bidder Complies YES _____ NO _____

COMPRESSOR FOR AIR HORNS: A Buell Model No 6540 maintenance free, Oil-less Air compressor shall be supplied and installed. This intermittent duty (6 minutes ON, 25 minutes OFF) compressor shall be dedicated for the air horn use only. The compressor shall generate 1.15 cubic feet per minute (CFM) of air volume at zero pounds per square inch and shall have a compression capacity of at least 125 pounds per square inch. The compressor shall run and stop automatically with a pressure switch that is set to come on at ninety-five (95) pounds per square inch and SHUT OFF at One hundred twenty-five (125) pounds per square inch. The compressor inlet port shall be filtered. The compressor shall supply compressed air to a pressure vessel listed below. The pressure vessel shall not exceed 3.0 gallons (693 cubic inches) of volume. Amperage draw shall never exceed 18 amperes at 12.0 volts, even at start up.

Bidder Complies YES _____ NO _____

The specified air horn compressor shall be located in the Streetside forward middle compartment.

Bidder Complies YES _____ NO _____



MODULE INTERIOR

ATTENDANT SEAT: There shall be an EVS Vacuum formed high back captain's seat mounted in the patient area. The seat shall be mounted per the requirements in the latest revision of KKK-A-1822. The seatbelt on the main part of the seat shall be an integrated, that is supplied and tested by the seat manufacturer as a complete package. Attendant seat shall have integrated child seat. Seatbelts shall be black in color.

Bidder Complies YES _____ NO _____

SEAT BASE: There shall be a powder coated metal seat that is tested to be utilized with the integrated Child Safety 4-point harness that is hidden behind the removable back pad. The metal base shall be concealed behind a substrate with mica laminate to be color keyed to the patient area interior. There shall be a flush mounted solid door on a stainless-steel hinge with a spring-loaded lever latch.

Bidder Complies YES _____ NO _____

AIR CONDITIONING EVAPORATOR CABINET: The patient cabin shall be equipped with a rear air conditioning and heat unit. The unit shall be wired, connected, and installed per the environmental section of this specification. A cabinet, specifically designed to fit, form, and function to the constraints set forth in the surrounding cabinet design and air exchange for cooling/heating performance requirements. The AC/Heat cabinet will be located behind the attendant seat at ceiling height. The AC/Heat delivery system will be free flowing and non-ducted. The design shall provide adequate air return to meet or exceed current revision of the Federal specification KKK-A-1822.

Bidder Complies YES _____ NO _____

LEFT FRONT ELECTRICAL CABINET: This cabinet shall be located behind the attendant seat and below the Air Conditioning unit. Access to the main circuit board shall be provided through the face of the cabinet facing the curbside. The access door shall be hinged along the right side with a non-locking lever type latch at the top.

The door shall open without interference with other cabinet doors or hardware.

Bidder Complies YES _____ NO _____

PLASTIC VENT: A fifteen square inch free air flow ventilation hole be cut into the above door. The edges of the cut out shall be banded. The hole shall be covered with an aesthetically appealing, molded plastic louver cover. The louver cover shall be black in color and secured with at least one No 8 screw in each corner.

Bidder Complies YES _____ NO _____



DOOR EDGE FINISH: The edges of the aforementioned door(s) shall be covered with anodized aluminum, U- shaped trim. The trim shall be miter cut and wrapped around the perimeter of the door (On ALL four sides), including the hinged side. The trim shall be bonded to the door edge and clamped. No screws or other mechanical fastener shall be used to fasten the trim work to the door(s). The corners of the doors shall be broken (rounded) after application. Vinyl "Iron on" or mica edge banding is not acceptable.

Bidder Complies YES_____NO_____

NON-LOCKING LATCH: A black positive latch shall be supplied and installed on the cabinet door. A small "preload" on the latch shall be imposed to prevent the door from rattling.

Bidder Complies YES_____NO_____

BULKHEAD CABINET: The front bulkhead wall shall have an open cabinet extending from the floor to a height of 45 inches, be 28 inches wide and 4 inches deep. This multipurpose cabinet interior shall be finished in high impact, white colored mica that is impervious to disinfectants and cleaners. The bottom at floor level shall have a 5lb fire extinguisher mounted on the left and two strapless "D" Oxygen holders mounted on the right. The upper section shall have space for the two Streamlight Vulcan flashlights to be mounted.

Bidder Complies YES_____NO_____

CURBSIDE GLOVE CABINET: The curbside upper cabinet is located on the curbside (right side) of the patient cabin, over the curbside entry doors. A three-box glove dispenser shall be built into the head end of this cabinet with a fixed partition between each box of gloves. The gloves shall dispense through oblong slots cut into the 3/8-inch-thick Lexan door. One door shall cover all three glove box bays, hinge across the top and feature a brass bodied, roller bearing type catch at the bottom.

Bidder Complies YES_____NO_____

RIGHT FRONT CABINET (I): The right front cabinet is hereinafter known as ALS cabinet. All fixed and adjustable shelf surfaces shall be covered in Easy Grip material. All fixed and adjustable shelf lips shall be covered with anodized aluminum trim. All shelves shall have a 3/4 lip. The ALS cabinet shall provide at least 21.0 cubic feet of storage and configured as follows.

Bidder Complies YES_____NO_____

: This cabinet shall be divided into two cabinets, upper (U8) and lower (L8) cabinets. Both cabinets will have inside/outside access.

Bidder Complies YES_____NO_____ALS CABINET



DUAL FLUSH LEXAN DOORS: Two opposite hinged doors shall be supplied on the aforementioned cabinets.

Bidder Complies YES _____ NO _____

HINGE ORIENTATION: The doors shall be hinged along the outside edge of each door.

Bidder Complies YES _____ NO _____

SHELF STANDARDS: The aforementioned cabinet shall be equipped with non-incremental, aluminum, C-shaped shelf standards.

Bidder Complies YES _____ NO _____

ADJUSTABLE SHELVES: There shall be a total of three adjustable shelves in the right front cabinet. Two shelves in the "U8" cabinet and one shelf in the lower "L8" cabinet. The shelves shall be finished in white colored laminate. The upper, lower and aisle side surfaces of the shelves shall be laminated. The shelves shall be secured to four shelf clips with Phillips head wood screws, from the bottom of the shelf. An anodized aluminum angle shall be securely fastened to the front edge of the shelves. The vertical leg of the angle shall provide a lip along the front edge.

Bidder Complies YES _____ NO _____

RIGHT REAR CABINET: The right rear exterior compartment specified herein shall be completely concealed from interior view by a right rear cabinet. All exposed surfaces of this cabinet shall be fully laminated over substrate matching main cabinet structures. The vertical outer corner shall feature a radius anodized aluminum trim. The trim shall originate from the top of the mated squad bench and terminate into the ceiling.

UPHOLSTERY PAD: An upholstered pad covering the entire forward-facing wall, over the squad bench shall be provided. The pad shall include at least 1/2" thick foam padding covered in the same heavy-duty vinyl covering specified for the squad bench cushions and the remaining upholstery package.

Bidder Complies YES _____ NO _____

SQUAD BENCH: A squad bench shall be installed on the curbside of the patient compartment. Seating shall be installed as described writing these specifications. All seat belts and anchorage shall comply with F.M.V.S.S. 209 and 210. The seatbelt color shall be black.

The Squad Bench shall comply with current KKK-A-1822. A back and head rest shall be supplied for all seated personnel along the squad bench.

Bidder Complies YES _____ NO _____



UNDER LID STOWAGE: The squad bench shall provide storage under the access lids. This multipurpose storage area shall be finished in high impact, white colored laminate. Must meet current Federal specification current KKK-A-1822.

Bidder Complies YES _____ NO _____

SQUAD BENCH LIDS: Two (Split) squad bench lids shall be supplied over the squad bench storage area.

Bidder Complies YES _____ NO _____

HINGE, SQUAD BENCH LID(S): All squad bench lids shall be installed with butt style, hinges. The hinges shall be through bolted for longevity of the vehicle. There shall be a minimum of two hinges per lid.

Bidder Complies YES _____ NO _____

LID LATCH: One latch to hold each lid down shall be supplied. The lid latch shall be stamped stainless steel construction and latches automatically by simply closing the bench lid.

Bidder Complies YES _____ NO _____

LID CHECKS: Each squad bench lid shall have a bi-directional gas spring lid check (Hold open). The force value selected, and ball stud locations shall provide lift assistance after twenty degrees of bench lid lift angle. The ball stud mounts shall be at least 10 millimeters.

Bidder Complies YES _____ NO _____

EDGE TRIM: The edge of the squad bench lid shall be finished with aluminum anodized "J" trim. The trim is to be supplied with countersunk holes to allow for screws to be installed flush, so the screw head does not catch anything.

Bidder Complies YES _____ NO _____

SHARPS AND TRASH: At the head of the squad bench shall be a built-in trash disposal area. A trash can shall be accessible under a red flip up lid, and a sharps container's circular opening shall be accessible through a round cutout in the squad bench lid. Both the trash can, and the sharps container may be removed from the squad bench by lifting up a sectioned portion of the squad bench lid.

Bidder Complies YES _____ NO _____



CABINET "U7/U7.5": An interior cabinet shall be provided above the squad bench, on the curb side of the vehicle. This multipurpose cabinet interior shall be finished in high impact, white colored mica that is impervious to disinfectants and cleaners. The cabinet shall have a single opening and one fixed divider, setback for door operation. The cabinet shall add at least 2.0 cubic feet of interior stowage accommodations described in the present revisions of the Federal specification KKK-A-1822 3.11.1.

Bidder Complies YES _____ NO _____

CABINETS, - Standard T-1

CABINET "U2": An upper, interior cabinet shall be provided directly over the action area of the Base wall cabinet. This multipurpose cabinet interior shall be finished in high impact, white colored laminate and have one adjustable shelf. Must meet current Federal specification KKK-A-1822.

Bidder Complies YES _____ NO _____

SLIDING POLYCARBONATE DOORS: The cabinet shall be equipped with two sliding 3/16" polycarbonate doors within a closed anodized aluminum track/frame. The sliding polycarbonate door track shall be an extruded, anodized aluminum shape designed to accommodate a flocked, felt type track for the doors to slide in and lightly resist movement. The mitered corners shall be splined together and riveted. The extrusion shape shall cover one half of one inch of cabinet fascia around the perimeter of the track frame.

Bidder Complies YES _____ NO _____

HANDLES, POLYCARBONATE DOORS: Full height, anodized aluminum, extruded drive on handles shall be supplied on each 3/16" door. The handle shall wrap around the leading edge of each door and mount with one-way angular, blind mounting teeth designed to be driven on.

ACTION AREA: The action area is a work surface located on the forward end of the Base Wall Cabinet and adjacent to the attendant seat. The work surface shall be at least 5.5 square feet. The work area height shall be 24 inches to 29 inches. The work surface shall have a three-quarter inch (3/4") high lip.

Bidder Complies YES _____ NO _____

A/A TRAY: There shall be a countertop action area forward at the wall cabinet. The countertop shall be a Corian type hard surface counter.

Bidder Complies YES _____ NO _____



CPR SEAT: A left side "CPR" side seat shall be provided on the street side and aligned with the primary patient's abdomen. The seat shall be at least twenty-four (24") inches wide and normal squad bench seat height.

Upholstered seat pads shall be located within the seat area for the seat, back, both arms and hips. The CPR seat area shall have rounded corners. The seatbelt color shall be red or orange in color.

Bidder Complies YES _____ NO _____

BACK REST: The CPR side seat shall feature a padded, fixed back rest with chamfered upper corners.

Bidder Complies YES _____ NO _____

CABINET "U3.5": An upper, interior cabinet shall be provided directly over the "Telemetry Area". This multipurpose cabinet interior shall be finished in high impact, white colored laminate with one adjustable shelf. Must meet current Federal specification KKK-A-1822.

Bidder Complies YES _____ NO _____

SLIDING POLYCARBONATE DOORS: The cabinet shall be equipped with two sliding 3/16" polycarbonate doors within a closed anodized aluminum track/frame. The sliding polycarbonate door track shall be an extruded, anodized aluminum shape designed to accommodate a flocked, felt type track for the doors to slide in and lightly resist movement. The mitered corners shall be splined together and riveted. The extrusion shape shall cover one half of one inch of cabinet fascia around the perimeter of the track frame.

Bidder Complies YES _____ NO _____

HANDLES, POLYCARBONATE DOORS: Full height, anodized aluminum, extruded drive on handles shall be supplied on each 3/16" door. The handle shall wrap around the leading edge of each door and mount with one-way angular, blind mounting teeth designed to be driven on.

TELEMETRY AREA: A telemetry area shall be located just rearward of the CPR seat. The countertop will be the same height as the action area and have a Corian type hard surface countertop.

Bidder Complies YES _____ NO _____

There will be a locking wall mounted 5 qt sharps container mounted on the rearward wall of the telemetry area.

Bidder Complies YES _____ NO _____



CABINET "L3.5": An interior cabinet shall be provided under the telemetry area on the street side. This multipurpose cabinet interior shall be finished in high impact, white colored laminate. Must meet current Federal specification KKK-A-1822.

Bidder Complies YES _____ NO _____

FULL DEPTH DRAWER: The drawer shall be full depth with locking slides. There shall be four adjustable dividers placed within the drawer.

Bidder Complies YES _____ NO _____

CABINET "U4": An interior cabinet shall be provided at the rearward end of the upper base cabinet on the street side. The inside of this cabinet will have a service panel to access the exhaust vent. This multipurpose cabinet interior shall be finished in high impact, white colored laminate with adjustable shelf. Must meet current Federal specification KKK-A-1822.

Bidder Complies YES _____ NO _____

SLIDING POLYCARBONATE DOORS: The cabinet shall be equipped with two sliding 3/16" polycarbonate doors within a closed anodized aluminum track/frame. The sliding polycarbonate door track shall be an extruded, anodized aluminum shape designed to accommodate a flocked, felt type track for the doors to slide in and lightly resist movement. The mitered corners shall be splined together and riveted. The extrusion shape shall cover one half of one inch of cabinet fascia around the perimeter of the track frame.

Bidder Complies YES _____ NO _____

HANDLES, POLYCARBONATE DOORS: Full height, anodized aluminum, extruded drive on handles shall be supplied on each 3/16" door. The handle shall wrap around the leading edge of each door and mount with one-way angular, blind mounting teeth designed to be driven on.

Bidder Complies YES _____ NO _____

CABINET "C4": An interior cabinet shall be provided at the rearward end of the base cabinet on the street side underneath cabinet "U4". This multipurpose cabinet interior shall be finished in high impact, white colored laminate with adjustable shelf. Must meet current Federal specification KKK-A-1822.

Bidder Complies YES _____ NO _____



SLIDING POLYCARBONATE DOORS: The cabinet shall be equipped with two sliding 3/16" polycarbonate doors within a closed anodized aluminum track/frame. The sliding polycarbonate door track shall be an extruded, anodized aluminum shape designed to accommodate a flocked, felt type track for the doors to slide in and lightly resist movement. The mitered corners shall be splined together and riveted. The extrusion shape shall cover one half of one inch of cabinet fascia around the perimeter of the track frame.

Bidder Complies YES _____ NO _____

HANDLES, POLYCARBONATE DOORS: Full height, anodized aluminum, extruded drive on handles shall be supplied on each 3/16" door. The handle shall wrap around the leading edge of each door and mount with one-way angular, blind mounting teeth designed to be driven on.

Bidder Complies YES _____ NO _____

RESTRAINT SYSTEM(S): The Seat Belt System(s) shall be in the following locations: Seatbelt color shall be black.

RESTRAINT SYSTEM(S): The three (3) 4-point black restraint shall be fully retractable and utilize four retract retractors for increased mobility. The restraint shall feature controlled deceleration technology and a single buckle for single point-of-release. The restraint shall meet the requirements of FMVSS 209 and 302 standards. The restraint shall have a built-in indicator to signify that the webbing has undergone a severe load and needs to be replaced.

There shall be two (2) 4-point restraints on the Squad Bench and one (1) 4-point restraints on the CPR Side Seat. The seatbelt color shall be black.

Bidder Complies YES _____ NO _____

SECONDARY PATIENT RESTRAINT SYSTEM: There shall be a location for a secondary patient on top of the squad bench located on the curbside interior of the patient area of the ambulance. To secure the patient there shall be three inertia style retractable straps that match up to three 9" sleeved buckles on the face of the squad bench and 5" sleeved retractors by the squad bench lid hinge. The straps and buckles shall be mounted to comply with the pull test requirements in the present revision of KKK-A-1822. Seatbelt color black. orange in color.

Bidder Complies YES _____ NO _____

FLOOR AND SUBSTRATE: The floor of the module shall be (3/4) thick non-wood product.

Bidder Complies YES _____ NO _____



FLOOR COVERING: The floor substrate shall be free of dents, voids, and moisture prior to application of the floor covering. The substrate sheet shall be cut from a 60-inch-wide by 144-inch-long oversized sheet. No substrate seams are allowed in high foot traffic areas. This means NO SEAMS are permitted within 132" of the rear access doors or near the side access door.

On longer bodies, only ONE seam is permitted as long as the full length of the seam is located directly over the center of a 0.250 x 2 x 3 box tube floor member AND the seam does not fall in the aforementioned "High Traffic" areas.

The floor covering shall be one piece throughout the patient cabin regardless of the body length. The flooring material shall be commercial grade sheet vinyl floor with coin shaped protrusions on the surface. The floor covering shall be Lonseal Loncoin II Flecks No 150 "Onyx " (Black). The main field of the flooring around the "coins", shall be textured to minimize the appearance of minor scratches and imperfections brought on by wear.

Bidder Complies YES _____ NO _____

FLOORING MAIN EDGE: The one-piece patient cabin floor covering material shall run the full width of the aisle space plus roll up (3") three inches along the Base wall cabinet, squad bench and the right rear cabinet (when applicable). Both roll-up areas shall be recessed approximately 1/2" into the face of the cabinets.

Bidder Complies YES _____ NO _____

REAR THRESHOLD: The rear threshold shall be made of 16 gauge brushed stainless steel sheet. The threshold shall conceal the end of the vapor sheet, sub floor, and flooring. The threshold shall mate to the top of the rear access door jamb and cover at least six inches of flooring. Installed over the stainless-steel threshold shall be two 2.5" wide "nonskid" tape, strips applied. The color of the tape shall be safety yellow with black diagonal stripes.

Bidder Complies YES _____ NO _____

C/S THRESHOLD: The C/S threshold shall be made of .100 polished aluminum diamond plate. Bidder Complies YES _____ NO _____

COT MOUNT HARDWARE

PRIMARY COT MOUNT: The main cot mount shall be a dual position; Stryker model No 6377. The mounts shall be set in the center of aisle and seven inches (7) left of center position.



COT FASTENER MOUNTING METHOD: All mounting bolts shall be 3/8" diameter, socket head cap screws with at least 16 threads per inch. All mounting blocks shall be supplied and manufactured by the cot mount manufacturer. The mounting blocks may protrude above the flooring surface by up to 3/16", as long as all of the edges are chamfered. The aforementioned cap screws shall not protrude above the upper surface of the mounting block.

All cap screws shall be bolted through 1/2 (.500) inch thick, 6061-T-6 Aluminum plate structure. One and one half (1-1/2) inch x six (6) inch thick plates shall either be MIG welded or Chuck structurally fastened to the floor grid for both cot mount and attendant seat fastening locations. All fastening hardware shall be either through bolted or tapped depending on under floor clearances due to chassis installed components. Mounting bolts shall not point toward fuel filler or fuel vent hoses, in accordance with good engineering practices set forth by the Society of Automotive Engineers and Ford's Qualified Vehicle Modifiers' program.

Bidders shall meet or exceed mechanical strength described in the aforementioned minimum fastening method. Material thickness and/or through bolt criteria is mandatory even if the vendor has current certification to A.M.D. Standard 004 utilizing lesser materials.

COT POSITION No 1: This cot position shall be set up for a primary wheeled cot set centered laterally (side to side) in the aisle. The longitudinal location shall be set 30 inches measured from the backrest of the attendant's seat (set all the way toward the front of the patient cabin) to the head of the primary cot frame, per current KKK-A-1822.

COT LOCATION No 2: This cot position shall be set up for a primary wheeled cot set approximately eight inches left of center laterally (side to side) in the aisle or as close to the left side wall cabinet as practical. The longitudinal location shall be set 30 inches measured from the backrest of the attendant's seat (set all the way toward the front of the patient cabin) to the head of the primary cot frame, per current Federal KKK-A-1822.

Bidder Complies YES _____ NO _____

PRIMARY COT: The aforementioned cot fastener shall be set up to use a Stryker Model No. Power-Pro

Cot. Bidder Complies YES _____ NO _____

COT HOOK: A Stryker manufactured ramped hook derived of solid aluminum shall be through bolted to the threshold at the rear access doors. The design intent is to prevent accidental cot roll off during loading and unloading a one-man cot. The hook shall snag a tubular drag bar that is built into the cot frame. The cot hook shall be placed in a position where the under carriage of the cot can be erected and locked into place before release of the drag bar.

Bidder Complies YES _____ NO _____



COT RETENTION FLOOR SUPPORT: There shall be structural support installed in floor framing to support the future installation of a Triple K Change Notice 10 compliant cot retention system.

Bidder Complies YES _____ NO _____

OXYGEN, AIR and VACUUM SYSTEMS

OXYGEN HOSES: All oxygen system service hoses, fittings and devices shall be made of nonferrous materials. Hoses used to pipe Medical Oxygen shall be electrically non-conductive, ¼ inside diameter with an abrasion resistant, green colored outer jacket. The hose manufacturer's name, part number, inside dimension and working pressure rating shall be permanently marked along the entire length of the hose. All hoses shall have a working pressure rating of at least 250 pounds per square inch, withstand a system test pressure of 150 PSI / 1033 kPa test prescribed in current Federal specification KKK-A-1822. Each ambulance shall be tested.

Bidder Complies YES _____ NO _____

OXYGEN OUTLETS - GENERAL: Each outlet shall be comprised of an "*Inlet Box*" and a "*Latch Plate*" as defined herein. The "*inlet box*" shall be a universal inlet service box with a 165 mm type "K" (3/8") OD Copper inlet pipe stub which is silver brazed to a brass, one piece, (1 5/16") inlet body. The "*inlet box*" shall be designed specifically for positive pressure gas service and feature a primary and secondary check valve. Each check valve shall be rated at 1,379 kPa (200psi).

The "*Latch Plate*" shall be inserted into the universal "*Inlet Box*". The "*Latch Plate*" is comprised of the outer cover plate and latching mechanism that will define the adapter type/Brand that will ultimately connect the patient to the oxygen system. The outlet cover shall be color coded GREEN in addition to having a clear permanent legend that identifies the gas type. Dual gas specific safety pins shall be integrated in the face of the outlet "*Latch Plate*" for safety.

Outlet adapter types shall be easily changed by simply removing the "*Latch plate*" specifically designed for brand "A" to brand "B" without any further plumbing changes.

As with all medical gas outlets specified herein, all outlets shall be hydrostatically tested and cleaned for oxygen service. All medical gas outlets specified herein shall be UL (Underwriters Laboratory) listed and CSA approved. All outlets will be subject to a line pressure of 50 PSI and shall be leak tested at 150 PSI Per Federal specification KKK-A-1822. Pressure drops across the outlet shall be less than 2.0 PSI at normal working pressure.

Bidder Complies YES _____ NO _____



OXYGEN OUTLET No 1: This outlet latch shall be designed to accept (Ohio) style, quarter turn / quick release adapters. This Oxygen outlet shall be provided where specified below.

Bidder Complies YES _____ NO _____

LOCATION: The Oxygen outlet shall be located in the primary action area switch and outlet

console. Bidder Complies YES _____ NO _____

OXYGEN OUTLET No 2: This outlet latch shall be designed to accept (Ohio) style, quarter turn / quick release adapters. This Oxygen outlet shall be provided where specified below.

Bidder Complies YES _____ NO _____

LOCATION: The Oxygen outlet shall be located in the primary action area switch and outlet

console. Bidder Complies YES _____ NO _____

OXYGEN OUTLET No 3: This outlet latch shall be designed to accept (Ohio) style, quarter turn / quick release adapters. This Oxygen outlet shall be provided where specified below.

Bidder Complies YES _____ NO _____

LOCATION: The Oxygen outlet shall be located in curb side wall, over the squad bench and near the curbside entry door.

Bidder Complies YES _____ NO _____

MAIN CYLINDER RESTRAINT No 1: One manufacturer supplied M-size compressed, medical gas cylinder shall be carried and secured, vertically inside the left front exterior compartment. The cylinder rack shall be through bolted to the back wall. A rust-free cylinder rack with (2) heavy duty pull style, web straps with quick spring-loaded release shall be type tested to AMD Test 003 Oxygen Tank Retention System Test. The cylinder valve shall also be visible and accessible from the inside through a clear polycarbonate door.

Bidder Complies YES _____ NO _____

NECK STRAP: There shall be an additional webbed strap looped onto the racks upper most securing strap. The strap is to have two loops. The bottom loop will be the section secured to the upper most strap and the upper loop shall be secured onto the neck of the oxygen or medical air bottle to help secure it in place in the case of an upward exertion.

Bidder Complies YES _____ NO _____



CYLINDER TYPE: This rack shall be for a MEDICAL OXYGEN cylinder. The oxygen system input hose shall be suspended over this rack. This input hose shall feature a nonferrous 9/16-18 RH bottle nut and regulator barb. This connection shall comply with the diameter index safety system (DISS) set forth by the Compressed Gas Association (CGA) for safety.

Bidder Complies YES_____NO_____

CYLINDER RACK LOCATION: The main oxygen cylinder shall be stored in the left front compartment. The cylinder rack shall be through bolted on the back wall, near the right-hand wall of the compartment. The cylinder neck shall be visible and accessible through the viewing window.

Bidder Complies YES_____NO_____

Cylinder Wrench: There shall be a cast aluminum main oxygen cylinder wrench installed in the compartment with the main oxygen cylinder rack. The wrench shall include a cable lanyard that secures the wrench to the compartment wall allowing enough length of cable to loosen and tighten the regulator fitting on the customer installed main oxygen cylinder. The wrench shall be stored in place with either a hat channel bracket or Velcro to keep it secured while the vehicle is in motion.

OXYGEN REGULATOR: Oxygen regulator, wall mounted above o2 bottle, with 24” braded hose extension. To be mounted in on a 45deg plate so regulator can be read from the inside of truck or from the outside compartment.

Bidder Complies YES_____NO_____

VACUUM (SUCTION) PANEL: A variable vacuum regulator and gauge panel shall be installed in the action area control panel. The vacuum regulator shall vary vacuum delivered to a 1200 cubic-centimeter collection jar specified below. The Vacuum gauge shall not be mounted on the collection jar itself.

Bidder Complies YES_____NO_____

COLLECTION JAR: The suction system shall be equipped with a shatter proof, graduated, 1200cc, transparent collection container. The container shall be regulated through the SSCOR panel and secured in a "boxed in" padded shelf.

Bidder Complies YES_____NO_____

COLLECTION JAR PLUMBING: The collection jar shall be connected directly to the regulator panel in the action area console.

Bidder Complies YES_____NO_____



SUCTION PUMP: The suction pump shall be installed in the left middle compartment, adjacent to the action area panel. The exhaust tube shall be routed to the outside of the vehicle. The pump shall be mounted on rubber vibration isolators to minimize any vibration noise emitted into the patient cabin. The pump shall provide a free air flow of at least 20 liters per minute and achieve a minimum of (11.81 in) Hg vacuum within four seconds after the suction tube is closed. This 49-state pump shall meet or exceed current Federal specification KKK-A-1822.

Bidder Complies YES _____ NO _____

SUCTION PUMP LOCATION: The suction pump shall be installed in the left front middle compartment. The pump shall be mounted to the ceiling of this compartment on rubber vibration isolators.

Bidder Complies YES _____ NO _____

EXTERIOR ENTRY AND COMPARTMENT DOOR HANDLES: Door handles to be relocated from standard location to upper/outer corner of door. Large chrome plated, die cast paddle handles shall be provided to open all module doors. Blind fasteners shall be used to fasten the handles to the door from the backside.

Blind Stabilizer pins shall be incorporated on the backside of the handle for alignment purposes. Every paddle handle shall have an isolation gasket between the paddle body and the door skin. All door skin surfaces shall be painted prior to installation of the handle hardware. All paddles, on single hung and leading double doors shall be locking type and keyed the same (unless specified otherwise). Trailing doors shall; have non-locking paddle handles, mounted on the outside of the door. The Handle shall have a bright chrome like finish mounted into the bright chrome dish. When the door is in the locked position, the handle shall extend when pulled like an automotive handle (free floating) to show the operator that the door is locked and needs to be unlocked to be opened. Systems that utilize a handle that does not free float shall not be accepted as it could bind up the inner hardware and shorten the life of the door operation and timing.

DOOR HANDLE COLOR: Door handles to be black in lieu of chrome.

INTERIOR ENTRY AND COMPARTMENT DOOR HANDLES: The interior handle shall be lever type. A Lock/Unlock lever shall be installed below the inside lever handle and be clearly marked Lock/Unlock. The inner chrome plated handle shall have a black powder coated cast aluminum bezel for strength.

Bidder Complies YES _____ NO _____

INTERIOR GRAB HANDLE COLOR: The interior grab handles listed below will be powder coated with anti- microbial, gray in color.

Bidder Complies YES _____ NO _____



CURB SIDE ENTRY DOOR GRAB HANDLE: The curbside entry door shall be equipped with a two point, 1 ¼ diameter, stainless steel with gray anti-microbial coating, handicap style grab handles to aid in door closure and entry assistance. The handle shall measure at least eighteen inches long. The handle shall run horizontally, directly above the inside door latch. The door handles shall be fastened directly to the horizontal door structure that is welded to the door assembly.

Bidder Complies YES _____ NO _____

REAR ACCESS DOOR GRAB HANDLES: Each rear access door shall be equipped with a two point, 1 ¼ diameter, stainless steel with gray anti-microbial coating, handicap style grab handles to aid in door closure and entry assistance. The handle shall measure at least twelve inches long. Shall be polyurethane black coated

The handle shall run horizontally, directly above the inside door latch. The door handles shall be fastened directly to the horizontal door structure that is welded to the door assembly.

Bidder Complies YES _____ NO _____

DOOR PANELS: The inside UPPER door panels shall be made of .080 aluminum diamond plate. The edge of the diamond plate shall be recessed into the door frame extrusion. The center panel shall be upholstery over a smooth aluminum substrate.

Bidder Complies YES _____ NO _____

CURBSIDE LOWER DOOR PANEL: The inside door panel shall be made of .080 aluminum diamond plate. The edges of the diamond plate shall be recessed into the door frame extrusion. The panels shall be fastened to the door frame with stainless steel, #10-32 UNF machine screws threaded into aircraft quality blind fasteners. Each screw shall have a neoprene lock washer.

Bidder Complies YES _____ NO _____

REAR ENTRY DOOR WINDOWS: The rear entry doors shall have an automotive style window. The window will be recessed in a factory stamped opening. The windows will be near flush. They will be in a fixed position. Each window will have a nominal area of 320 square inches.

Bidder Complies YES _____ NO _____

SIDE ENTRY DOOR WINDOW: The curb side (Right) entry door shall be equipped with an automotive style window. The window will be recessed in a factory stamped opening. The window will be near flush. The window will be fixed position. All glass shall be tinted safety glass.

Bidder Complies YES _____ NO _____



TALK THROUGH WINDOW: The Cab to Module communications window shall be provided. Bidder Complies YES_____NO__

LOCKING PIN: The sliding cab to patient area window shall have a locking pin consisting of metal 1/4" pin with a lanyard retainer to keep from losing the pin when not latched. The pin shall be from the driver's side of the window. The pin shall meet or exceed current Federal specification KKK-A-1822.

Bidder Complies YES_____NO_____

ACTION AREA LIGHTING: A 12-volt LED light shall be provided directly over the forward, street side work surface. A 12-inch swivel fixture shall be provided. The light shall have an on/off rocker switch on the body of the light housing.

Bidder Complies YES NO_____

LOCATION: The light shall be mounted to the action area. Bidder Complies YES_____NO__

UPHOLSTERY MATERIALS: All padding and upholstered seating shall be covered in 36-ounce vacuum form ready vinyl. Sewn seams in the seat covers and cushions shall be minimized. Upon request, the manufacturer shall be capable of supplying vacuum formed, seamless vinyl covered upholstery. The color shall be color keyed to the laminate color selections made.

SEAT / BACKREST CORE MATERIAL: The vinyl covered foam shall meet current Federal Specification KKK-A-1822. Seat cushions shall be ergonomically contoured. All core material shall be open cell, high resilience foam.

Bidder Complies YES_____NO_____

TROUGH COVER: All upholstered pad that is built to cover the trough running down the center line of the vehicle separating the curbside and streetside of the patient compartment shall be manufactured of 1/4" luan non voided plywood with padding and covered with 36-ounce vinyl. The color of the vinyl shall be the same as the remainder of the upholstery in the patient area. The cover shall be fastened to the headliner using stainless steel screws with washers that will accept button covers that are color matched to the trough cover.

Bidder Complies YES_____NO_____



UPHOLSTERY JOINERY TYPE: All padding and upholstered seating shall feature upholstery covered foam that eliminates sewn, visible seams. All cushion corners shall be vinyl wrapped. NO sewn seams are permitted, even at the corners. Seat cushion vinyl shall be pre-formed to the cushion shape to eliminate ALL visible seams. Seat cushions with welting/piping and sewn corner seams are not acceptable since blood and other liquid form biological discharge can penetrate the seam holes and reside in the foam. All vinyl surfaces shall be pulled tight against the foam, utilizing a hardwood plywood backing board. Loose fitting vinyl coverings are not acceptable.

Bidder Complies YES _____ NO _____

FULL CUSHIONS: The post and wheel cups normally placed on the squad bench for secondary stretchers shall be DELETED in favor of full seat cushions without cutouts. The seat cushions shall be the same size as the squad bench lid and WITHOUT cutouts. The user chooses to use a backboard in lieu of a stretcher for a secondary patient.

Bidder Complies YES _____ NO _____

HEAD PROTECTION - CURB SIDE ACCESS DOOR: A seamless pad specifically designed to protect the head during egress is required. The pad shall consist of a two-inch-thick foam sheet over a hardwood plywood backing board and covered in seamless vinyl upholstery.

Bidder Complies YES _____ NO _____

HEAD PROTECTION - REAR ACCESS DOORS: A seamless pad specifically designed to protect the head during egress is required and shall comply with current Federal Specification KKK-A-1822. The pad shall consist of a two-inch-thick foam sheet over a hardwood plywood backing board and covered in seamless vinyl upholstery.

Bidder Complies YES _____ NO _____

PAINT

Paint Color TBD at final: Color will be a lime green/yellow on top 2/3 of unit and dark gray on lower 1/3. Paint codes TBD at final.

100% PAINT FILM COVERAGE: All stages of primer and paint shall cover all surfaces. Hinge mating surfaces on the doors and jambs shall be painted. Bare aluminum and primer only preparation is not acceptable under door hinges. Doors shall be painted without actuation handles installed and doors removed from body. Paint film thickness to be no less than 4.1 mil thickness.



PAINT SYSTEM TYPE: The paint shall be Poly-Urethane type electrostatic application process without exception.

An electrostatic paint spray system is a highly efficient technology for the application of paint to specific work pieces. Negatively charged atomized paint particles and a grounded work piece create an electrostatic field that draws the paint particle to the work piece, minimizing overspray.

For this technology, an ionizing electrode, typically located at the paint gun atomizer tip, causes paint particles to pick up additional electrons and become negatively charged. As the coating is deposited on the work piece, the charge dissipates through the ground and returns to the power supply, completing the circuit. The electrostatic field influences the path of the paint particles. Because the charged particles are attracted to the grounded work piece, overspray is significantly reduced. Paint particles that pass a work piece can be attracted to and deposited on the back of the piece. This phenomenon is known as "wrap."

MECHANICAL ADHESION PROMOTER: The entire module shall be degreased. Degreaser shall be applied to manufacturers recommendations. The module body is to be inspected for flaws and imperfections, and to assure built to order specifications. All surfaces shall be initial sanded with 180 grit paper and all imperfections repaired.

CHEMICAL ADHESION PROMOTER: The module shall be hot water washed at (140 degrees or greater). Then the aluminum Body shall be treated with Alumiprep 33 acid etching followed by a complete De-ionized body rinse. To ensure all surfaces are cleaned, this step shall be repeated a second time. The entire unit shall be wet coated with Alodine 5700 conversion coating, and de ionized water mixed. The module body is baked at 160 degrees to dry.

PRIMER: The module shall then have 2 coats of epoxy primer. The unit is then baked at 140-degree metal temperature for one hour. The module body will then undergo any bodywork or filler that is required at transition(s). A third coat of epoxy primer is applied and cured. The module body will then be final sanded prior to Paint color application. Primer shall be sanded with 320 grit paper to assure flat, orange peel free surface.

TOPCOAT (PAINT): Entire module shall be degreased. Degreaser shall be applied to manufactures recommendations. Two coats of BTLV High Solids color shall be applied.

CLEAR COAT: The clear coat shall be manufactured by the same company as the primer and base coat. Two coats of "clear coat" polyurethane shall be applied per the manufacturer's instructions.

3M POLISHING SYSTEM: Prior to 100% paint cure, the paint on the ambulance body shall be sanded to 1200 grit and polished flat per 3Ms Perfect-It product program for smooth finish.

Bidder Complies YES _____ NO _____

CORROSION: Anti-electrolysis procedures include but are not limited to the following.

- 1) Ensure all bare substrate is dry and free from contamination.



- 2) If bare substrate is showing signs of corrosion/oxidation, sand and remove. Use 180 grit until area is removed.
- 3) Thoroughly blow off areas to remove sand dust and metal shavings.
- 4) Thoroughly degrease to be pre-primed using the wipe-on, wipe-off method with clean white rags. (Use good quality automotive Degreaser)
- 5) Apply Wash primer CR using a brush to all mated surfaces. Allow to flash for 15 minutes at 70 deg Fah. Mix wash primer CR 1:1 with wash-hardener.
- 6) Apply Urethane caulk to all mated surfaces before assembly to reduce the possibility of corrosion.

EXTERIOR FASTENERS: All screw sites require a replaceable nylon insert for the fastener to thread into. This will isolate the dissimilar metals. Each hole shall be treated with an Electrolysis Corrosion Control compound prior to installation of the nylon inserts. All exterior screws shall be stainless steel.

UNDERCOATING: The bottoms side of the module shall be undercoated, with an exception to any area affected by exhaust system direct heat. Application standards for the undercoating shall be achieved or exceeded as directed by QVM or governing standards.

Bidder Complies YES _____ NO _____

REFLECTIVE TAPE: The module door frames shall have a three-quarter inch (3/4") wide white reflective tape applied to the door frame interior. The tape shall illuminate the outline shape of the door when the door is opened.

Bidder Complies YES _____ NO _____

REFLECTIVE / PRISMATIC TAPE: The aforementioned center step shall have a bright, conspicuous prismatic, reflective tape strip applied to the rearward facing edge of the step. The tape shall have alternated colors (Red and White). The tape color shall begin and end in Red, and each segment shall measure between seven and nine inches.

Bidder Complies YES _____ NO _____

ROOF PAINT: Color match to sides, full roof paint, top finish to exceed industry standard of 5 plus mill thickness.

Bidder Complies YES _____ NO _____

DRIP RAILS: A bright drip rail shall be provided over each compartment. Full height compartments are exempt because the perimeter roof rail drip rails will cover these compartments.

Bidder Complies YES _____ NO _____



DRIP RAILS: A bright drip rail shall be provided over each compartment. Full height compartments are exempt because the perimeter roof rail drip rails will cover these compartments.

Bidder Complies YES _____ NO _____

OWNER'S MANUAL: There shall be shipped loose with each completed unit a DVD data file with pertinent information from the build of the vehicle.

Bidder Complies YES _____ NO _____

SAFETY PLACARDS: There shall be installed in the chassis cab and patient area descriptive placards in durable materials to remind occupants of the clearance height of the ambulance, to fasten seatbelts and to refrain from smoking.

Bidder Complies YES _____ NO _____

FIRE EXTINGUISHER: Two (5) five-pound A-B-C type fire extinguishers shall be supplied loose with the vehicle on delivery.

Bidder Complies YES _____ NO _____

REFLECTOR PACKAGE: Six reflectors shall be supplied on the outside of the module body. The reflectors shall be located at skirt line level and the area size shall be at least 3.75 square inches. Each side shall have one AMBER forward reflector and one RED rearward reflector. The rear of the body shall have one RED reflector, located just above the diamond plate kick plate.

Bidder Complies YES _____ NO _____

OXYGEN REGULATOR: A fixed output medical regulator shall be supplied with the apparatus. The output shall be fixed via a single chamber pressure setting which can produce a 50 psi +/- 5psi at 7.25 LPM. The output of the regulator may vary as the tank pressure lowers or flow rate is changed. The regulator shall have a CGA 540 thread for the bottle and a 9/16- 18 TPI threaded male connector for the input hose to the system.

Bidder Complies YES _____ NO _____

Optional Award(s)

GRAPHICS: Graphics to match fleet design. Design/Rendering to be attached to bid spec. Graphics to be added separately priced line item as an additional purchase option to add